

DIN EN 295-7:2013-05 (E)

Vitrified clay pipe systems for drains and sewers - Part 7: Requirements for pipes and joints for pipe jacking

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Requirements for pipes for pipe jacking | 6 |
| 4.1 | Materials, manufacture, water absorption and appearance | 6 |
| 4.2 | Dimensions | 7 |
| 4.2.1 | General | 7 |
| 4.2.2 | Internal diameter | 7 |
| 4.2.3 | Tolerance on the declared internal diameter | 7 |
| 4.2.4 | Continuity of invert | 8 |
| 4.2.5 | External diameter | 8 |
| 4.2.6 | Length | 9 |
| 4.2.7 | Squareness of ends | 9 |
| 4.2.8 | Deviation from straightness | 9 |
| 4.3 | Strength | 9 |
| 4.3.1 | Crushing strength (FN) | 9 |
| 4.3.2 | Bending tensile strength | 10 |
| 4.3.3 | Compressive strength | 10 |
| 4.3.4 | Jacking strength | 10 |
| 4.3.5 | Maximum working jacking load | 11 |
| 4.3.6 | Fatigue strength under cyclic load | 11 |
| 4.4 | Watertightness | 11 |
| 4.5 | Airtightness | 11 |
| 4.6 | Chemical resistance | 12 |
| 4.7 | Hydraulic roughness | 12 |
| 4.8 | Abrasion resistance | 12 |
| 4.9 | Resistance against high pressure water jetting | 13 |
| 5 | Requirements for joints for pipe jacking | 13 |
| 5.1 | Joint materials | 13 |
| 5.1.1 | Rubber sealing elements | 13 |
| 5.1.2 | Polyurethane sealing elements | 13 |
| 5.1.3 | Stainless steel sleeves | 13 |
| 5.1.4 | Polypropylene sleeve couplings | 13 |
| 5.1.5 | Other materials | 13 |
| 5.2 | Load transfer rings | 13 |
| 5.3 | Watertightness of joints under deflection and shear load | 14 |
| 5.3.1 | General | 14 |
| 5.3.2 | Test pressures | 14 |
| 5.4 | Angular deflection | 14 |
| 5.5 | Shear resistance | 14 |
| 5.6 | Chemical and physical resistance to effluent | 14 |
| 5.7 | Thermal cycling stability | 15 |
| 5.8 | Long-term thermal stability | 15 |
| 6 | Common requirements for pipes and joints | 15 |

| | | |
|---|--|-----------|
| 6.1 | Reaction to fire | 15 |
| 6.2 | Durability | 15 |
| 6.3 | Dangerous substances | 16 |
| 7 | Designation | 16 |
| 8 | Marking | 16 |
| 9 | Evaluation of conformity | 17 |
| 9.1 | General | 17 |
| 9.2 | Initial type testing | 17 |
| 9.3 | Factory production control (FPC) | 17 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU | | |
| | Construction Products Directive | 18 |
| ZA.1 | Scope and relevant characteristics | 18 |
| ZA.2 | Procedures for the attestation of conformity of vitrified clay pipes and joints for pipe jacking . | 20 |
| ZA.2.1 | Systems of attestation of conformity | 20 |
| ZA.2.2 | EC declaration of conformity | 21 |
| ZA.3 | CE marking | 21 |
| ZA.3.1 | General | 21 |
| ZA.3.2 | CE marking on the product | 21 |
| ZA.3.3 | CE marking in the accompanying documents | 22 |
| | Bibliography | 25 |