

DIN EN 295-6:2013-05 (E)

Vitrified clay pipe systems for drains and sewers - Part 6: Requirements for components of manholes and inspection chambers

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Requirements for components for manholes and inspection chambers	6
4.1	Materials, manufacture, water absorption and appearance	6
4.1.1	Vitrified clay	6
4.1.2	Rubber sealing material	6
4.1.3	Polyurethane sealing materials	6
4.1.4	Polypropylene couplings	6
4.1.5	Materials of other components	6
4.2	Internal diameter	6
4.2.1	Chamber rings and raising pieces	6
4.2.2	Pipeline connections	6
4.3	Height	6
4.4	Angle of curvature and radius of channel bends	7
4.5	Branch angles of channel junctions	7
4.6	Crushing strength (FN)	7
4.7	Bending tensile strength	7
4.8	Bond strength of adhesive used for fixing fired clay parts together	7
4.9	Fatigue strength under cyclic load	7
4.10	Chemical resistance	7
4.11	Water tightness of assembled components	7
4.12	Joint systems	8
5	Common requirements for manholes and inspection chambers	8
5.1	Reaction to fire	8
5.2	Durability	8
5.3	Dangerous substances	8
6	Designation	9
7	Marking	9
7.1	Manhole and inspection chamber components	9
7.2	Joints	10
8	Evaluation of conformity	10
8.1	General	10
8.2	Initial type testing	10
8.3	Factory production control (FPC)	10
Annex A (informative) Examples of manholes and inspection chambers		11
A.1	Manhole	11
A.2	Inspection chamber	11
Annex B (informative) Manhole stability		13

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive	14
ZA.1 Scope and relevant characteristics	14
ZA.2.1 Systems of attestation of conformity	16
ZA.2.2 EC declaration of conformity	17
ZA.3 CE marking	17
ZA.3.1 General	17
ZA.3.2 CE marking on the product	18
ZA.3.3 CE marking in the accompanying documents	18
Bibliography	21