DIN EN 295-6:2013-05 (E)

Vitrified clay pipe systems for drains and sewers - Part 6: Requirements for components of manholes and inspection chambers

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Requirements for components for manholes and inspection chambers 6
4.1 Materials, manufacture, water absorption and appearance 6
4.1.1 Vitrified clay 6
4.1.2 Rubber sealing material 6
4.1.3 Polyurethane sealing materials 6
4.1.4 Polypropylene couplings 6
4.1.5 Materials of other components 6
4.2 Internal diameter 6
4.2.1 Chamber rings and raising pieces 6
4.2.2 Pipeline connections 6
4.3 Height 6
4.4 Angle of curvature and radius of channel bends 7
4.5 Branch angles of channel junctions 7
4.6 Crushing strength (FN) 7
4.7 Bending tensile strength 7
4.8 Bond strength of adhesive used for fixing fired clay parts together 7
4.9 Fatigue strength under cyclic load 7
4.10 Chemical resistance 7
4.11 Water tightness of assembled components 7
4.12 Joint systems 8

5 Common requirements for manholes and inspection chambers 8
5.1 Reaction to fire 8
5.2 Durability 8
5.3 Dangerous substances 8

6 Designation 9

7 Marking 9
7.1 Manhole and inspection chamber components 9
7.2 Joints 10

8 Evaluation of conformity 10
8.1 General 10
8.2 Initial type testing 10
8.3 Factory production control (FPC) 10

Annex A (informative) Examples of manholes and inspection chambers 11

A.1 Manhole 11
A.2 Inspection chamber 11

Annex B (informative) Manhole stability 13

Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive 14

ZA.1 Scope and relevant characteristics 14

ZA.2.1 Systems of attestation of conformity 16

ZA.2.2 EC declaration of conformity 17

ZA.3 CE marking 17

ZA.3.1 General 17

ZA.3.2 CE marking on the product 18

ZA.3.3 CE marking in the accompanying documents 18

Bibliography 21