

DIN EN 14364:2013-05 (E)

Plastics piping systems for drainage and sewerage with or without pressure - Glass-reinforced thermosetting plastics (GRP) based on unsaturated polyester resin (UP) - Specifications for pipes, fittings and joints

Contents		Page
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	8
3	Terms, definitions and symbols	9
4	General requirements	17
4.1	Classification	17
4.1.1	General	17
4.1.2	Categories	17
4.1.3	Nominal size	17
4.1.4	Nominal stiffness	17
4.1.5	Nominal pressure	17
4.2	Materials	18
4.2.1	General	18
4.2.2	Reinforcement	18
4.2.3	Resin	19
4.2.4	Aggregates and fillers	19
4.2.5	Elastomers	19
4.2.6	Metals	19
4.3	Wall construction	19
4.3.1	Inner layer	19
4.3.2	Structural layer	19
4.3.3	Outer layer	19
4.4	Appearance	20
4.5	Reference conditions for testing	20
4.5.1	Temperature	20
4.5.2	Properties of water for testing	20
4.5.3	Loading conditions	20
4.5.4	Preconditioning	20
4.5.5	Measurement of dimensions	20
4.6	Elapsed time for determination of long-term properties, (x)	20
4.7	Joints	20
4.7.1	General	20
4.7.2	Types of joint	20
4.7.3	Flexibility of the jointing system	21
4.7.4	Sealing ring	21
4.7.5	Adhesives	21
5	Pipes	21
5.1	Geometrical characteristics	21
5.1.1	Diameter	21
5.1.2	Wall thickness	26
5.1.3	Length	26
5.2	Mechanical characteristics	27

5.2.1	Initial specific ring stiffness	27
5.2.2	Long-term specific ring stiffness under wet conditions	28
5.2.3	Initial resistance to failure in a deflected condition	29
5.2.4	Ultimate long-term resistance to failure in a deflected condition	31
5.2.5	Initial specific longitudinal tensile strength	32
5.2.6	Initial failure and design pressures for pressure pipes	34
5.2.7	Long-term failure pressure	36
5.2.8	Resistance to strain corrosion	38
5.3	Marking	40
6	Fittings	41
6.1	General	41
6.2	Bends	42
6.2.1	Classification of bends	42
6.2.2	Dimensions and tolerances of bends	42
6.3	Branches	46
6.3.1	Classification of branches	46
6.3.2	Dimensions and tolerances of branches	47
6.4	Reducers	49
6.4.1	Classification of reducers	49
6.4.2	Dimensions and tolerances of reducers	50
6.4.3	Mechanical characteristics of tapered section laminate	51
6.5	Non Pressure Saddles	52
6.5.1	Classification of saddles	52
6.5.2	Dimensions and tolerances of saddles	53
6.6	Flanges	54
6.6.1	Classification of flanges	54
6.6.2	Dimensions and tolerances for flanged adaptors	55
6.7	Marking	56
7	Joint performance	57
7.1	General	57
7.1.1	Interchangeability	57
7.1.2	Test temperature	57
7.1.3	Non-pressure piping	57
7.2	Dimensions	57
7.3	Non-end-load-bearing flexible joints with elastomeric sealing rings	57
7.3.1	General	57
7.3.2	Requirements	57
7.3.3	Number of test pieces for type test purposes	58
7.3.4	Test pieces	58
7.4	End-load-bearing flexible joints with elastomeric sealing rings	59
7.4.1	General	59
7.4.2	Performance requirements for locked-socket-and-spigot joints with elastomeric sealing rings	59
7.5	Wrapped or cemented joints	61
7.5.1	General	61
7.5.2	Performance requirements	61
7.5.3	Number of test pieces for type test purposes	62
7.5.4	Test pieces	62
7.6	Bolted flange joints	63
7.6.1	General	63
7.6.2	Performance requirements	63
7.6.3	Number of test pieces for type test purposes	64
7.6.4	Test pieces	64
7.6.5	Joint assembly details	64
7.6.6	Torque resistance	64
Annex A	(normative) Test method for the resistance to bending and pressure of end-thrust loaded joints in pipe systems	66
A.1	Principle	66
A.2	Apparatus	66

A.3	Test pieces	66
A.4	Test temperature	67
A.5	Calculation of the bending load F	67
A.5.1	General	67
A.5.2	Calculation of F, if applied in the horizontal plane	67
A.5.3	Calculation of F, if applied in the vertical plane	68
A.6	Procedure	69
A.7	Test report	69
Bibliography		71