

ISO 4377:2012-08 (E)

Hydrometric determinations - Flow measurement in open channels using structures - Flat-V weirs

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols	3
5	Characteristics of flat-V weirs	4
6	Installation	4
6.1	Selection of site	4
6.2	Installation conditions	7
6.3	Weir structure	8
6.4	Downstream conditions	8
7	Maintenance	8
8	Measurement of head(s)	9
8.1	General	9
8.2	Stilling (gauge) wells	9
8.3	Zero setting	11
8.4	Location of head measurement sections	13
9	Discharge relationships	14
9.1	Equations of discharge	14
9.2	Effective heads	15
9.3	Shape factors	16
9.4	Coefficient of velocity	16
9.5	Conditions for modular/drowned flow	18
9.6	Drowned flow reduction factor	21
9.7	Limits of application	28
10	Computation of discharge	29
10.1	General	29
10.2	Successive approximation method	29
10.3	Coefficient of velocity method	31
10.4	Accuracy	32
11	Uncertainties in flow determination	32
11.1	General	32
11.2	Combining uncertainties	33
11.3	Uncertainty in the discharge coefficient $u^*(CDe)$ for the flat-V weir	34
11.4	Uncertainty in the drowned flow reduction factor $u^*(Cdr)$	34
11.5	Uncertainty in the effective head	35
11.6	Uncertainty budget	35
11.7	Variation of uncertainty with flow and uncertainty in mean daily flow and the daily flow volume	36

12	Examples	37
12.1	Example 1 -- Computation of modular flow at low discharge	37
12.2	Example 1 -- Uncertainty in computed discharge	39
12.3	Example 2 -- Computation of drowned flow at high discharge	41
12.4	Example 2 -- Uncertainty in computed discharge	43
Annex A (normative) Velocity distribution		46
Annex B (informative) Introduction to measurement uncertainty		47
Annex C (informative) Performance guide for hydrometric equipment for use in technical standards		56
Bibliography		59