

DIN EN ISO 11296-7:2013-05 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 7: Lining with spirally-wound pipes (ISO 11296-7:2011)

Contents		Page
Foreword		3
Introduction		4
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Symbols and abbreviated terms	8
4.1	Symbols	8
4.2	Abbreviated terms	8
5	Pipes at the "M" stage	8
5.1	Materials	8
5.2	General characteristics	9
5.3	Material characteristics	9
5.4	Geometric characteristics	10
5.5	Mechanical characteristics	11
5.6	Physical characteristics	11
5.7	Jointing	11
5.8	Marking	11
6	Fittings at the "M" stage	12
7	Ancillary components	12
8	Fitness for purpose of the installed lining system at the "I" stage	12
8.1	Materials	12
8.2	General characteristics	12
8.3	Material characteristics	12
8.4	Geometric characteristics	12
8.5	Mechanical characteristics	12
8.6	Physical characteristics	13
8.7	Additional characteristics	13
8.8	Preparation of samples	13
8.9	Adhesives	13
9	Installation practice	13
9.1	Preparatory work	13
9.2	Storage, handling and transportation of profiled plastics strips and fittings	13
9.3	Equipment	13
9.4	Installation	14
9.5	Process-related inspection and testing	15
9.6	Lining termination	15
9.7	Reconnecting to existing manholes and laterals	15
9.8	Final inspection and testing	15
9.9	Documentation	15

Annex A (normative) Spirally-wound pipe -- Test method for watertightness in a deflected condition	16
Annex B (informative) Examples of methods for reconnecting and sealing laterals to SWO pipe	19
Bibliography	20