

ISO 4359:2013-02 (E)

Flow measurement structures - Rectangular, trapezoidal and U-shaped flumes

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 2 |
| 5 | Flume types and principles of operation | 3 |
| 6 | Installation | 6 |
| 6.1 | Selection of site | 6 |
| 6.2 | Installation conditions | 8 |
| 7 | Maintenance | 10 |
| 8 | Measurement of head | 11 |
| 8.1 | General | 11 |
| 8.2 | Location of head measurement(s) | 11 |
| 8.3 | Gauge wells | 11 |
| 8.4 | Zero setting | 12 |
| 9 | General equations for discharge | 12 |
| 9.1 | Discharge based on critical flow in the flume throat | 12 |
| 9.2 | Discharge based on observed upstream head | 13 |
| 9.3 | Calculation of stage-discharge relationships | 27 |
| 9.4 | Approach velocity and coefficient of velocity | 27 |
| 9.5 | Selection of flume size and shape | 28 |
| 10 | Rectangular-throated flume | 30 |
| 10.1 | Description | 30 |
| 10.2 | Location of head measurement section | 30 |
| 10.3 | Provision for modular flow | 30 |
| 10.4 | Evaluation of discharge for a given observed upstream head | 31 |
| 10.5 | Computation of stage-discharge relationship | 35 |
| 10.6 | Limits of application | 35 |
| 11 | Trapezoidal-throated flumes | 36 |
| 11.1 | Description | 36 |
| 11.2 | Location of head measurement section | 36 |
| 11.3 | Provision for modular flow | 37 |
| 11.4 | Evaluation of discharge -- Coefficient method | 37 |
| 11.5 | Computation of stage-discharge relationship | 40 |
| 11.6 | Limits of application | 42 |
| 12 | U-throated (round-bottomed) flumes | 43 |
| 12.1 | Description | 43 |
| 12.2 | Location of head measurement section | 44 |
| 12.3 | Provision for modular flow | 44 |
| 12.4 | Evaluation of discharge -- Coefficient method | 44 |

| | | |
|------|--|----|
| 12.5 | Computation of stage-discharge relationship | 48 |
| 12.6 | Limits of application | 50 |
| 13 | Uncertainties of flow measurement | 51 |
| 13.1 | General | 51 |
| 13.2 | Combining measurement uncertainties | 52 |
| 13.3 | Percentage uncertainty of discharge coefficient $u^*(C)$ for critical-depth flumes | 54 |
| 13.4 | Uncertainty budget | 54 |
| 14 | Example of uncertainty calculations | 55 |
| 14.1 | General | 55 |
| 14.2 | Characteristics -- Gauging structure | 55 |
| 14.3 | Characteristics -- Discharge calculation | 55 |
| 14.4 | Characteristics -- Discharge coefficient | 55 |
| 14.5 | Characteristics -- Gauged head instrumentation | 56 |
| 14.6 | Characteristics -- Throat width | 56 |
| 14.7 | Overall uncertainty in discharge | 57 |
| | Annex A (informative) Simplified head-discharge relationships for flume | 58 |
| | Annex B (informative) Introduction to measurement uncertainty | 63 |
| | Annex C (informative) Sample measurement performance for use in hydrometric worked examples | 72 |
| | Annex D (informative) Spreadsheets for use with this International Standard | 75 |
| | Bibliography | 77 |