ISO 16422:2014-02 (E)

Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Specific ations

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 5
4.1 Symbols 5
4.2 Abbreviations 6

5 Material 6
5.1 General 6
5.2 Rework material 6

6 Effect of materials on water quality 6

7 Material classification 6
7.1 MRS value 6
7.2 Design coefficient 6
7.3 Design stress 7

8 Classification and selection of pipes 7
8.1 Classification 7
8.2 Calculation of wall thickness 8
8.3 Determination of the allowable operating pressure, PFA, for temperatures up to 45 °C 8
8.4 Derating factor related to application of the system 8

9 General requirements for pipes 10
9.1 Appearance 10
9.2 Opacity 10

10 Geometrical characteristics for pipes 10
10.1 Measurement 10
10.2 Outside diameters and wall thicknesses 10
10.3 Pipes with integral sockets 10
10.4 Plain ends 11

11 Mechanical characteristics of pipes 11
11.1 Resistance to hydrostatic pressure 11
11.2 Resistance to external blows at 0 °C 12
11.3 Ring stiffness 12

12 Physical characteristics 12

13 Mechanical characteristics of assemblies, including joints 13
13.1 Assemblies with non-end-load-bearing joints 13
13.2 Short-term pressure test for leak tightness of assemblies 13

13.3 Short-term negative pressure test for leak tightness of assemblies 15
13.4 Long-term pressure test for leak tightness 15
13.5 End-load-bearing joints -- Pressure and bending test for leak tightness and strength 16

14 Elastomeric seals 16

15 Marking 16

Annex A (normative) Establishment of the pipe material classification 17

Annex B (informative) Minimum depth of engagement of sockets 18

Annex C (normative) Temperature derating factor 21

Annex D (informative) Ring stiffness of pipes 22

Annex E (informative) Determination of the long-term test pressure by creep consideration 24

Annex F (informative) Determination of axial and tangential orientation factor 25