

ISO 16422:2014-02 (E)

Pipes and joints made of oriented unplasticized poly(vinyl chloride) (PVC-O) for the conveyance of water under pressure - Specific ations

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	5
4.1	Symbols	5
4.2	Abbreviations	6
5	Material	6
5.1	General	6
5.2	Rework material	6
6	Effect of materials on water quality	6
7	Material classification	6
7.1	MRS value	6
7.2	Design coefficient	6
7.3	Design stress	7
8	Classification and selection of pipes	7
8.1	Classification	7
8.2	Calculation of wall thickness	8
8.3	Determination of the allowable operating pressure, PFA, for temperatures up to 45 °C	8
8.4	Derating factor related to application of the system	8
9	General requirements for pipes	10
9.1	Appearance	10
9.2	Opacity	10
10	Geometrical characteristics for pipes	10
10.1	Measurement	10
10.2	Outside diameters and wall thicknesses	10
10.3	Pipes with integral sockets	10
10.4	Plain ends	11
11	Mechanical characteristics of pipes	11
11.1	Resistance to hydrostatic pressure	11
11.2	Resistance to external blows at 0 °C	12
11.3	Ring stiffness	12
12	Physical characteristics	12
13	Mechanical characteristics of assemblies, including joints	13
13.1	Assemblies with non-end-load-bearing joints	13
13.2	Short-term pressure test for leak tightness of assemblies	13

13.3	Short-term negative pressure test for leak tightness of assemblies	15
13.4	Long-term pressure test for leak tightness	15
13.5	End-load-bearing joints -- Pressure and bending test for leak tightness and strength	16
14	Elastomeric seals	16
15	Marking	16
Annex A (normative) Establishment of the pipe material classification		17
Annex B (informative) Minimum depth of engagement of sockets		18
Annex C (normative) Temperature derating factor		21
Annex D (informative) Ring stiffness of pipes		22
Annex E (informative) Determination of the long-term test pressure by creep consideration		24
Annex F (informative) Determination of axial and tangential orientation factor		25