

DIN EN 124-6:2015-09 (E)

Gully tops and manhole tops for vehicular and pedestrian areas - Part 6: Gully tops and manhole tops made of polypropylene (PP), polyethylene (PE) or unplasticized poly(vinyl chloride) (PVC-U)

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms, definitions, symbols and abbreviations | 7 |
| 3.1 | Terms and definitions | 7 |
| 3.2 | Symbols and abbreviations | 8 |
| 4 | Materials | 8 |
| 4.1 | General | 8 |
| 4.2 | Combination of elements made of different materials | 9 |
| 4.3 | UV stability (artificial weathering resistance) | 9 |
| 4.3.1 | General | 9 |
| 4.3.2 | Carbon black requirements for UV resistant PE and PP | 10 |
| 4.3.3 | Titanium dioxide requirements for UV resistant PVC-U | 10 |
| 4.4 | Metallic fixing | 10 |
| 5 | Requirements | 10 |
| 5.1 | Design and performance requirements | 10 |
| 5.2 | Material specific characteristics for gully tops and manhole tops made of PE, PP, and PVC-U | 11 |
| 5.2.1 | Reaction to fire | 11 |
| 5.2.2 | Effect of heating | 11 |
| 5.2.3 | Deflection under load | 12 |
| 5.2.4 | Impact resistance | 12 |
| 5.2.5 | Durability | 12 |
| 5.2.6 | Dangerous substances | 13 |
| 6 | Testing | 13 |
| 6.1 | General | 13 |
| 6.2 | Effect of heating | 13 |
| 6.3 | Deflection under load | 13 |
| 6.4 | Impact resistance | 13 |
| 7 | Assessment and verification of constancy of performance -- AVCP | 14 |
| 7.1 | General | 14 |
| 7.2 | Type testing | 15 |
| 7.2.1 | General | 15 |
| 7.2.2 | Test samples, testing and compliance criteria | 15 |
| 7.2.3 | Test reports | 17 |
| 7.2.4 | Shared other party results | 17 |
| 7.3 | Factory production control (FPC) | 18 |
| 7.3.1 | General | 18 |
| 7.3.2 | Requirements | 18 |
| 7.3.3 | Product specific requirements | 21 |
| 7.3.4 | Initial inspection of factory and of FPC | 22 |
| 7.3.5 | Continuous surveillance of FPC | 22 |

| | | |
|--|---|----|
| 7.3.6 | Procedure for modifications | 23 |
| 8 | Designation | 23 |
| 9 | Marking | 24 |
| Annex A (normative) Characteristics of glass fibres used for reinforcement of PP polymer | | 26 |
| Annex B (normative) Test of deflection under load | | 27 |
| B.1 | Test samples | 27 |
| B.2 | Deflection test load, FD | 27 |
| B.3 | Apparatus | 27 |
| B.3.1 | Testing machine | 27 |
| B.3.2 | Test blocks | 27 |
| B.3.3 | Deflection measurement device(s) | 27 |
| B.4 | Procedure | 27 |
| B.4.1 | Procedure for testing rectangular and circular covers/gratings | 27 |
| B.4.2 | Procedure for testing multiple and triangular covers/gratings | 28 |
| B.4.3 | Observations and reporting | 28 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation | | 29 |
| ZA.1 | Scope and relevant characteristics | 29 |
| ZA.2 | Procedures for AVCP of gully tops and manhole tops made of PP, PE or PVC-U) | 31 |
| ZA.2.1 | Systems of AVCP | 31 |
| ZA.2.2 | Declaration of performance (DoP) | 33 |
| ZA.3 | CE marking and labelling | 35 |
| Bibliography | | 38 |