ISO 16631:2016-03 (E)

Ductile iron pipes, fittings, accessories and their joints compatible with plastic (PVC or PE) piping systems, for water applications and for plastic pipeline connections, repair and replacement

Contents

Page

Foreword v

1 Scope 1

2 Normative references 2

3 Terms and definitions 2

4 Technical requirements 6
4.1 General 6
4.2 General requirements 6
4.2.1 Pipes and fittings nominal sizes 6
4.2.2 Surface condition 6
4.2.3 Types of joints and interconnection 6
4.2.4 Materials in contact with water intended for human consumption 7
4.3 Pressure classification and dimensional requirements 8
4.3.1 Pressure classification 8
4.3.2 Diameter 8
4.3.3 Wall thickness 9
4.3.4 Length 9
4.3.5 Straightness of pipes 9
4.4 Material characteristics 9
4.4.1 Tensile properties 9
4.4.2 Brinell hardness 10
4.5 Coatings and linings for pipes 10
4.5.1 General 10
4.5.2 External coatings 10
4.5.3 Internal linings 10
4.6 Coatings and linings for fittings and accessories 10
4.7 Marking 11
4.8 Packaging and handling 11

5 Leaktightness requirements 11
5.1 Pipes and fittings 11
5.2 Flexible joints 12
5.2.1 General 12
5.2.2 Ductile iron socket assembled with ductile iron spigot end 12
5.2.3 Ductile iron socket assembled with plastic spigot end 13

6 Test methods 17
6.1 Dimensions 17
6.1.1 External diameter 17
6.1.2 Wall thickness 17
6.1.3 Length 17
6.2 Straightness of pipes 17
6.3 Tensile test 18
6.3.1 Centrifugally cast pipes 18
6.3.2 Fittings and accessories 18
6.3.3 Test bar 18

6.3.4 Equipment and test method ... 18
6.3.5 Test results ... 18
6.3.6 Test frequency ... 18
6.4 Brinell hardness ... 18
6.5 Works leaktightness test of pipes and fittings ... 19
6.5.1 General ... 19
6.5.2 Centrifugally cast pipes ... 19
6.5.3 Fittings ... 19

7 Type tests ... 19
7.1 Type tests on ductile iron spigot ends ... 19
7.1.1 Leaktightness of joints to internal pressure ... 19
7.1.2 Leaktightness of joints to external pressure ... 20
7.1.3 Leaktightness of joints to negative internal pressure ... 21
7.2 Type tests on plastic spigot ends ... 21
7.2.1 General ... 21
7.2.2 Leaktightness of joints to internal hydrostatic pressure ... 21
7.2.3 Leaktightness of joints to negative internal pressure ... 23
7.2.4 Long-term hydrostatic strength test for joints of fittings for PE pipes ... 24
7.2.5 Pull out test at 25 °C for restrained joints for PE pipes ... 24
7.2.6 Long-term hydrostatic strength test for joints of fittings for PVC pipe ... 25

8 Tables of dimensions ... 25
8.1 Pipes ... 25
8.1.1 General ... 25
8.1.2 External diameters ... 26
8.1.3 Wall thickness ... 26
8.1.4 Pipes length ... 27
8.1.5 Sockets for push-in flexible joints ... 27
8.2 Fittings ... 28
8.2.1 General ... 28
8.2.2 Wall thickness ... 28
8.2.3 Sockets for push-in socketed fittings ... 28
8.2.4 Flanged socket ... 28
8.2.5 Flanged spigot ... 29
8.2.6 Collars ... 30
8.2.7 Double socket bend 90° (1/4) ... 31
8.2.8 Double socket bend 45° (1/8) ... 32
8.2.9 Double socket bend 22°30' (1/16) ... 33
8.2.10 Double socket bend 11°15' (1/32) ... 34
8.2.11 Double socket tee with flanged branch ... 35
8.2.12 All socket tee ... 37
8.2.13 Double socket taper ... 39

Annex A (informative) External coating ... 41

Annex B (informative) Internal lining ... 42

Annex C (normative) Stiffness determination ... 43

Annex D (normative) Quality assurance ... 44

Annex E (informative) Safety factors ... 45

Annex F (normative) Water pipeline systems incorporating ductile iron and plastic components46
Annex G (informative) Environmental aspects ... 47

Bibliography ... 48