

DIN EN 14405:2017-05 (E)

Characterization of waste - Leaching behaviour test - Up-flow percolation test (under specified conditions)

Contents		Page
European foreword		4
Introduction		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Principle	9
5	Reagents	9
6	Equipment	10
6.1	General	10
6.2	Laboratory equipment	10
7	Sample pretreatment	11
7.1	General	11
7.2	Sample preparation	11
7.3	Test portion	12
7.4	Determination of dry residue	13
8	Procedure	13
8.1	Temperature	13
8.2	Preparation	13
8.3	Packing of the column	13
8.4	Start-up of the test	15
8.5	Collection of additional eluate fractions	16
8.6	Further preparation of the eluates for analysis	18
8.7	Blank test	18
9	Calculations	18
10	Performance characteristics	19
11	Test report	20
11.1	General	20
11.2	General data	20
11.3	Leaching test conditions	20
11.4	Analytical report	20
11.5	Results of the leaching test	21
Annex A (informative) Illustration of the column and accompanying equipment		22
Annex B (informative) Suggestions for packing the column, water saturation and establishment and checking of equilibrium conditions		23
B.1	General	23
B.2	Guidelines on column filling and packing	23

B.3	Water saturation	23
B.4	Equilibration and checking of equilibrium conditions	24
Annex C (informative) Background for the choices made in developing this percolation test		26
C.1	Introduction	26
C.2	Particle size / particle size distribution	27
C.3	Column dimensions	27
C.4	Flow mode (up-flow/down-flow)	27
C.5	Flow rate of the leachant	27
C.6	L/S ratio and eluate fractions collected/duration of the test	28
C.7	Nature of the leachant	28
C.8	Temperature	29
C.9	Beneficial use of the test results	29
Annex D (informative) Repeatability and reproducibility data		30
D.1	Materials used in the interlaboratory comparison study	30
D.2	Interlaboratory comparison results	30
Bibliography		40