

DIN EN ISO 11298-2:2018-05 (E)

Plastics piping systems for renovation of underground water supply networks - Part 2: Lining with continuous pipes (ISO 11298-2:2018)

Contents		Page
European foreword		3
Foreword		4
Introduction		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Symbols and abbreviated terms	8
4.1	Symbols	8
4.2	Abbreviated terms	9
5	Pipes at the “M” stage	9
5.1	Material	9
5.2	General characteristics	9
5.3	Material characteristics	9
5.4	Geometrical characteristics	9
5.5	Mechanical characteristics	9
5.6	Physical characteristics	9
5.7	Joining	9
5.8	Marking	9
5.9	Regional requirements for pipes	10
6	Fittings at the “M” stage	10
6.1	Requirements	10
6.2	Marking	10
6.3	Regional requirements for fittings	10
7	Ancillary components	10
8	Fitness for purpose of the system for pipes and fittings at the “I” stage	10
9	Installation practice	10
9.1	Preparatory work	10
9.2	Storage, handling and transport	10
9.3	Equipment	11
9.3.1	Butt fusion equipment and debanding equipment	11
9.3.2	Pipe rollers	11
9.3.3	Winching and rod-pulling equipment	11
9.3.4	Pipe entry guides	11
9.3.5	Electrofusion equipment	12
9.3.6	Inspection equipment	12
9.3.7	Lifting equipment	12
9.4	Installation	12
9.5	Process-related inspection and testing	13
9.6	Lining termination	13
9.7	Reconnection to the existing pipeline system	13
9.8	Final inspection and testing	13
9.9	Documentation	13
Annex A (normative) Layered pipes		14
Bibliography		15