

ISO 11296-2:2018-02 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 2: Lining with continuous pipes

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	2
5	Pipes at the "M" stage	2
5.1	Material	2
5.2	General characteristics	2
5.3	Material characteristics	3
5.4	Geometrical characteristics	3
5.5	Mechanical characteristics	3
5.6	Physical characteristics	3
5.7	Joining	3
5.8	Marking	3
5.9	Regional requirements for pipes	3
6	Fittings at the "M" stage	3
6.1	Requirements	3
6.2	Marking	3
6.3	Regional requirements for fittings	3
7	Ancillary components	3
8	Fitness for purpose of the system for pipes and fittings at the "I" stage	4
9	Installation practice	4
9.1	Preparatory work	4
9.2	Storage, handling and transport	4
9.3	Equipment	4
9.3.1	Butt fusion equipment and de-beading equipment	4
9.3.2	Pipe rollers	5
9.3.3	Winching and rod-pulling equipment	5
9.3.4	Pipe entry guides	5
9.3.5	Electrofusion equipment	5
9.3.6	Inspection equipment	5
9.3.7	Lifting equipment	5
9.4	Installation	5
9.5	Process-related inspection and testing	6
9.6	Lining termination	6
9.7	Reconnection to the existing pipeline system	6
9.8	Final inspection and testing	6
9.9	Documentation	6

Annex A (normative) Layered pipes	7
Bibliography	8