ISO 9912-4:2018 (E)

Agricultural irrigation equipment — Filters for microirrigation — Part 4: Granulated media filters

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Design and construction requirements

- 4.1 General
- 4.2 Inlet and expansion space chamber
- 4.3 Media chamber
- 4.4 Collection (underdrain) and back flushing unit
- 4.5 Prefiltration element
- 4.6 Back flushing control
- 4.6.1 Mandatory requirements
- 4.6.2 Optional features

5 Resistance of the filter to internal hydrostatic pressure

- 5.1 General
- 5.2 Preparation
- 5.3 Static pressure test
- 5.4 Cyclic pressure test
- 5.5 Collection (underdrain) and back flushing unit resistance to buckling or tearing

6 Clean pressure drop test

- 6.1 General
- 6.2 Flow rates and test sequence
- 6.3 Filter media
- 6.4 Prescreening
- 6.5 Inlet and outlet pressures
- 6.6 Test duration
- 6.7 Report

7 Back flushing tests

- 7.1 Back flushing parameters
- 7.2 Media escape test

8 Automatic back flushing and controller

- 8.1 Back flushing initiation
- 8.2 Flushing control mechanism test
- 8.2.1 Mechanism activated by pressure drop
- 8.2.2 Mechanism activated by duration of operation
- 8.2.3 Mechanism activated by volume of filtered water
- 8.2.4 Mechanism activated by another physical quantity
- 8.3 Operation of the protective device

9 Information to be supplied by the manufacturer

- 9.1 General
- 9.2 Filter data
- 9.3 Back flushing controller

Annex A (informative) Types of irrigation media filters

Annex B (informative) Granulated media

B.1 General
B.2 Rough media classification
B.2.1 General
B.2.2 Grain size and particle size distribution
B.2.3 Other common guidelines
B.3 Maintenance

Page count: 16