

ISO 11297-3:2018 (E)

Plastics piping systems for renovation of underground drainage and sewerage networks under pressure — Part 3: Lining with close-fit pipes

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
3.1	General
3.2	Techniques
3.3	Characteristics
3.4	Materials
3.5	Product stages
3.6	Service conditions
3.7	Joints
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Pipes at the “M” stage
5.1	Materials
5.1.1	Virgin material
5.1.2	Reprocessible and recyclable material
5.1.2.1	Reprocessible material
5.1.2.2	Recyclable material
5.2	General characteristics
5.2.1	Appearance
5.2.2	Colour
5.3	Material characteristics
5.4	Geometric characteristics
5.5	Mechanical characteristics
5.6	Physical characteristics
5.7	Jointing
5.8	Marking
5.9	Regional requirements for pipes
6	Fittings at the “M” stage
6.1	Requirements
6.2	Marking
6.3	Regional requirements for fittings
7	Ancillary components
8	Fitness for purpose of the installed lining system at the “I” stage
8.1	Materials
8.2	General characteristics
8.3	Material characteristics
8.4	Geometric characteristics
8.5	Mechanical characteristics
8.6	Physical characteristics
8.7	Additional characteristics

8.8	Sampling
8.9	Regional requirements for the installed lining system
9	Installation practice
9.1	Preparatory work
9.2	Storage, handling and transport of pipes and fittings
9.3	Equipment
9.3.1	Butt fusion and debearing equipment
9.3.2	Reduction equipment
9.3.3	Pipe skids/rollers
9.3.4	Winching and rod-pulling equipment
9.3.5	Pipe entry guides
9.3.6	Reforming equipment
9.3.7	Electrofusion equipment
9.3.8	Inspection equipment
9.3.9	Lifting equipment
9.4	Installation
9.5	Process-related inspection and testing
9.6	Lining termination
9.7	Reconnection to existing manholes and laterals
9.8	Final inspection and testing
9.9	Documentation
Annex A	(normative) Factory-folded heat-reverted polyethylene (PE) pipe — Determination of memory ability
A.1	General
A.2	Principle
A.3	Testing
A.3.1	Sampling
A.3.2	Procedure
A.3.3	Requirements
A.4	Test report

Page count: 16