

ISO 21268-3:2019 (E)

Soil quality — Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials — Part 3: Up-flow percolation test

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Reagents and materials
6	Apparatus
7	Sample pre-treatment
7.1	Preparation of laboratory sample and specification of particle size
7.2	Preparation of the test sample
7.3	Test portion
7.4	Determination of dry matter content
8	Procedure
8.1	Temperature
8.2	Preparation of the eluent
8.3	Preparation of the column
8.4	Packing of the column
8.5	Start of the test
8.6	Sample Collection and Liquid/Solid separation step
8.7	Collection of additional eluate fractions
8.8	Further preparation of the eluates for analysis
8.9	Blank test
9	Calculation
10	Test report
11	Analytical determination
11.1	General
11.2	Blank test information
12	Performance characteristics
12.1	General
12.2	Validation trials performed in Japan
12.2.1	Round robin tests performed in accordance with ISO/TS 21268-3:2007
12.2.2	Robustness testing and validation results considering equilibration period and flow rate
12.3	Validation results obtained in Germany (DIN 19528[5])
12.3.1	General
12.3.2	Results for validation trial 1
12.3.3	Results for validation trial 2

Annex A (informative) Suggestions for packing the column, water saturation and establishment of equilibrium conditions

- A.1 General**
- A.2 Column filling and packing**
- A.3 Water saturation**

Annex B (informative) Justification of the choices made in developing the test procedure

- B.1 General**
- B.2 Column dimensions**
- B.3 Leachant flow direction**
- B.4 Leachant flow rate**
- B.5 Nature of the leachant**
- B.6 L/S ratio**
- B.7 Temperature**
- B.8 Beneficial use of the test results**

Annex C (informative) Calculation of centrifugation duration depending on centrifugation speed and rotor dimensions

- C.1 General**
- C.2 Calculations**

Annex D (informative) Additional information on robustness testing and validation results based on waste materials

Page count: 34