DIN EN 13598-1:2020-12 (E)

Plastics piping systems for non-pressure underground drainage and sewerage - Unplasticized poly(vinyl chloride) (PVC- U), polypropylene (PP) and polyethylene (PE) - Part 1: Specifications for ancillary fittings and shallow chambers

Contents

Page

European foreword 4

1 Scope 6

2 Normative references 7

3 Terms and definitions 9

4 Symbols and abbreviations 12
4.1 Symbols 12
4.2 Abbreviations 12

5 Material 12
5.1 Ancillary fittings 12
5.2 Shallow chambers 13
5.3 Sealing ring retaining components 13

6 General characteristics 13
6.1 Appearance 13
6.2 Colour 13
6.3 Assemblies 13

7 Geometrical characteristics 13
7.1 General 13
7.2 Dimensions 13
7.2.1 General 13
7.2.2 Design lengths 14
7.2.3 Dimensions of ancillary fittings 14
7.2.4 Dimensions of shallow chambers 14
7.3 Additional requirements for sealed access fittings 14

8 Mechanical characteristics 14

9 Physical characteristics 16
9.1 Injection moulded ancillary fittings 16
9.2 Fabricated ancillary fittings 16

10 Performance requirements 17

11 Sealing rings 19

12 Adhesives 19

13 Marking and additional documentation 19
13.1 General 19
13.2 Minimum required marking, sealed access fittings and rodding tees 19
13.3 Minimum required marking, mechanical saddles 20
13.4 Minimum required marking, shallow chambers 20
13.5 Additional documentation, shallow chambers 21

13.6 Additional documentation, mechanical saddles 21

Annex A(normative) Utilization of non-virgin material for shallow chambers 22

A.1 Utilization of non-virgin materials 22
A.2 Material characteristics 24

Annex B(normative) Test methods for mechanical saddles 26

B.1 General 26
B.2 Test equipment 26
B.3 Procedures 27
B.3.1 Resistance to vertical load - pipe stop test 27
B.3.2 Mechanical strength 28
B.3.3 Tightness under deformation 29

Annex C(normative) Resistance to vertical loading of shallow chambers 31

Bibliography 32