

DIN EN 12457-3:2021-03 (E)

Characterization of waste - Leaching - Compliance test for leaching of granular waste materials and sludges - Part 3: Two stage batch test at a liquid to solid ratio of 2 l/kg and 8 l/kg for materials with high solid content with particle size below 4 mm (with or without size reduction)

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
3.1	leaching test	7
3.2	leachant	7
3.3	eluate	7
3.4	single batch leaching test	7
3.5	serial batch leaching test	7
3.6	liquid to solid ratio L/S (abbreviation : L/S)	7
3.7	liquid waste	7
3.8	sludge	7
3.9	monolithic waste	7
3.10	granular waste	7
3.11	dry matter content ratio (abbreviation : DR)	7
3.12	moisture content ratio (abbreviation MC)	8
3.13	laboratory sample	8
3.14	test sample	8
3.15	test portion	8
4	Compliance test	8
4.1	Principle	8
4.2	Equipment and reagents	8
4.3	Sampling strategy and sample preparation	9
5	Procedure	11
5.1	Testing conditions	11
5.2	Description of the procedure	11
5.3	Further preparation of the eluates for analysis	13
5.4	Blank test for the verification of the leaching procedure	13
6	Calculation	13
6.1	Expression of the results	13
6.2	First step batch at L/S = 2	14
6.3	Second step batch at L/S = 8	14
7	Documentation and test report	14
7.1	Sample preparation	14
7.2	Production of eluate	15
7.3	Analytical determination	15
7.4	Calculations and blank test information	16
8	Performance characteristics	16

8.1	Objective of the validation	16
8.2	Validation study	16
8.3	Validation results	17
8.4	Summary of the performance characteristics evaluation	20
Annex A(informative) Information on the influence on the test results of the parameters that affect leaching		22
Annex B(informative) Test for determining whether waste is in the liquid state		24
Annex E(informative) Example of a specific liquid-solid separation procedure for soil sample		28
Annex ZA (Informative) National deviation A from France		29
Bibliography		30