ISO 4360:2020 (E)

Hydrometry — Open channel flow measurement using triangular profile weirs

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Principle

6 Installation

- 6.1 General
- 6.2 Selection of site
- 6.3 Installation conditions
- 6.3.1 General
- 6.3.2 Measuring structure
- 6.3.3 Approach channel
- 6.3.4 Downstream channel

7 Maintenance

8 Measurement of head(s)

- 8.1 General
- 8.2 Location of head measurement(s)
- 8.2.1 Modular (free) flow
- 8.2.2 Non-modular (drowned) flow
- 8.3 Gauge wells
- 8.4 Zero setting
- 8.5 Dimensions

9 Discharge characteristics

- 9.1 Formulae of discharge
- 9.1.1 Modular (free) flow
- 9.1.2 Non-modular flow
- 9.2 Coefficients
- 9.2.1 Coefficient of discharge, Cd
- 9.2.2 Coefficient of velocity for modular flow, Cv
- 9.2.3 Non-modular flow reduction factor, f, with crest tappings
- 9.2.4 Non-modular flow reduction factor, f, with tailwater recorder
- 9.3 Limitations

10 Uncertainties of flow measurement

- 10.1 General
- 10.2 Combining measurement uncertainties
- 10.3 Uncertainty of discharge coefficient u(Cd) for the triangular profile weir
- 10.4 Uncertainty budget

11 Example

- 11.1 General
- 11.2 Characteristics — Gauging structure
- 11.3 Characteristics — Gauged head instrumentation
- 11.4 Discharge coefficient

11.5 Discharge calculation
11.6 Uncertainty statement

Annex A (informative) Introduction to measurement uncertainty

A.1 General
A.2 Confidence limits and coverage factors
A.3 Random and systematic error
A.4 Measurement standards
A.5 Evaluation of Type-A uncertainty
A.6 Evaluation of Type-B uncertainty
A.6.1 General
A.6.2 Triangular distribution
A.6.3 Rectangular distribution
A.6.4 Normal probability distribution
A.6.5 Bimodal probability distribution
A.7 Combined uncertainty value, uc

Annex B (informative) Sample measurement performance for use in hydrometric worked examples

Annex C (informative) Spreadsheet for use with this document

C.1 General
C.2 Structure of spreadsheet

Page count: 30