

ISO 22066:2020 (E)

Water quality — Determination of total cyanide — Method using segmented flow injection, in-line ultraviolet digestion analysis by gas diffusion and amperometric detection

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Interferences |
| 5.1 | Interferences by oxidizing agents |
| 5.2 | Interferences by sulfide |
| 6 | Reagents |
| 7 | Apparatus |
| 8 | Sampling and sample preparation |
| 8.1 | Oxidizing agent |
| 8.2 | Sulfide removal |
| 8.3 | Preservation |
| 9 | Procedure |
| 9.1 | Flow system set up |
| 9.2 | Reagent blank measurement |
| 9.3 | Checking the suitability of the segmented flow analysis system |
| 9.3.1 | Cyanide electrode stabilization |
| 9.3.2 | Performance verification of the system |
| 9.4 | Calibration |
| 9.5 | Sample measurement |
| 9.5.1 | Cyanide measurement |
| 10 | Calculations |
| 11 | Expression of results |
| 12 | Test report |
| Annex A | (informative) Example of a segmented flow analysis system |
| Annex B | (normative) Determination of the real cyanide concentration in the potassium cyanide solution (6.5.1) or potassium tetracyanozincate solution (6.6.1) |
| B.1 | Additional reagents |
| B.2 | Determination of cyanide concentration in potassium cyanide solution (6.5.1) |
| Annex C | (informative) Performance data |