

ISO 3716:2021-10 (E)

Hydrometry - Functional requirements and characteristics of suspended-sediment samplers

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Requirements of samplers | 1 |
| 5 | Characteristics of suspended-sediment samplers | 3 |
| 6 | Types of samplers | 3 |
| 6.1 | Open containers | 3 |
| 6.2 | Vertical and horizontal cylinder instantaneous trap samplers | 3 |
| 6.3 | Weighted bottle samplers | 4 |
| 6.4 | Pumping samplers | 5 |
| 6.4.1 | General | 5 |
| 6.4.2 | Fixed-orifice pumping samplers | 5 |
| 6.4.3 | Moveable-orifice samplers | 6 |
| 6.5 | Single-stage samplers | 6 |
| 6.6 | Point-integrating samplers | 7 |
| 6.7 | Depth-integrating samplers | 7 |
| 6.8 | Clean samplers | 8 |
| 6.9 | Sand-flux samplers | 9 |
| 7 | Models of samplers | 10 |
| Bibliography | | 13 |