

ISO 21052:2021-11 (E)

Restrained joint systems for ductile iron pipelines - Calculation rules for lengths to be restrained

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and symbols | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Symbols | 3 |
| 4 | Thrust restraint principles, calculation rules and general specification | 4 |
| 4.1 | Thrust forces | 4 |
| 4.2 | Calculation rules and general specification | 4 |
| 4.3 | Standard jointing systems offer no longitudinal restraint | 5 |
| 4.4 | Restrained joint systems | 5 |
| 4.5 | Length to be restrained | 5 |
| 4.6 | Restrained design method | 5 |
| 4.7 | Gravity thrust blocks | 6 |
| 5 | Thrust force | 6 |
| 5.1 | Internal hydrostatic pressure in straight pipes | 6 |
| 5.2 | Internal hydrostatic pressure in bends | 6 |
| 5.3 | Internal hydrostatic pressure in other configurations | 7 |
| 6 | Restrained joints | 8 |
| 6.1 | Principle | 8 |
| 6.2 | Conservative design | 8 |
| 6.3 | Required prevailing site conditions | 8 |
| 7 | Unit frictional force, F_s | 8 |
| 7.1 | Static frictional force | 8 |
| 7.2 | Values of soil cohesion | 9 |
| 8 | Polyethylene encasement and PU coating and other extruded organic coatings | 10 |
| 9 | Unit bearing resistances, R_s | 10 |
| 9.1 | Lateral resistance, passive soil pressure | 10 |
| 9.2 | Design value of passive soil pressure | 10 |
| 9.3 | Empirical values of passive soil pressure | 11 |
| 10 | Application to common situations | 14 |
| 10.1 | Horizontal bends | 14 |
| 10.2 | Vertical down bends | 15 |
| 10.3 | Vertical up bends | 15 |
| 10.4 | Tees | 16 |
| 10.5 | Reducers | 17 |
| 10.6 | Dead ends | 17 |
| 10.7 | Encroaching restrained lengths | 17 |
| 10.8 | Equal angle vertical offset (θ) | 18 |
| 10.9 | Combined horizontal equal angle bends (θ) | 19 |
| 10.10 | Combined horizontal unequal angle bends | 20 |
| 10.11 | Combined vertical equal angle offsets (θ) | 21 |
| | 10.11.1 Pipeline under obstruction | 21 |
| | 10.11.2 Pipeline over obstruction | 22 |
| 11 | Restrained lengths | 22 |

| | | |
|---------------------|---|-----------|
| 12 | Installation and laying instruction | 22 |
| 12.1 | Select backfill considerations..... | 22 |
| 12.1.1 | Backfill material versus native soil support characteristics..... | 22 |
| 12.1.2 | Swamps or marshes..... | 22 |
| 12.2 | Combining thrust blocks/anchor blocks and restrained joints..... | 22 |
| 12.3 | Pipe in a casing..... | 23 |
| 12.3.1 | Restrained lengths inside casing..... | 23 |
| 12.3.2 | Balancing the thrust force with restraining lengths outside the casing..... | 23 |
| 12.4 | Future excavations..... | 23 |
| Annex A | (informative) Dimensions and unit weights of pipes filled with water for preferred class | 24 |
| Annex B | (informative) Soil classification chart | 25 |
| Bibliography | | 26 |