

DIN EN 14525:2022-12 (E)

Ductile iron and steel wide tolerance couplings and flange adaptors for use with pipes of different materials: ductile iron, Grey iron, steel, PVC-U, PVC-O, PE, fibre - cement

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Technical requirements | 10 |
| 4.1 | General | 10 |
| 4.1.1 | Diameter range | 10 |
| 4.1.2 | Surface condition and repairs | 10 |
| 4.1.3 | Types of joints and interconnection | 11 |
| 4.1.4 | Materials in contact with water intended for human consumption | 11 |
| 4.2 | Dimensional requirements | 12 |
| 4.2.1 | Minimum wall thickness of ductile iron couplings and flange adaptors | 12 |
| 4.2.2 | Minimum wall thickness of steel couplings and flange adaptors | 12 |
| 4.2.3 | Joint gap and depth of engagement | 13 |
| 4.2.4 | Angular deflection | 14 |
| 4.3 | Material characteristics | 14 |
| 4.3.1 | Ductile iron | 14 |
| 4.3.2 | Mild steel for couplings and flange adaptors (DN600 to DN800 only) | 14 |
| 4.3.3 | Fastener for couplings and flange adaptors | 15 |
| 4.4 | Coatings | 15 |
| 4.5 | Product information | 15 |
| 4.5.1 | Marking requirements | 15 |
| 4.5.2 | Additional information | 16 |
| 4.6 | Water tightness | 16 |
| 4.6.1 | Couplings and flange adaptors | 16 |
| 4.6.2 | Joints | 16 |
| 5 | Performance requirements for joints | 16 |
| 5.1 | General | 16 |
| 5.2 | Pressure rating | 17 |
| 5.3 | Water tightness of flexible joints | 17 |
| 5.3.1 | General - performance tests principles | 17 |
| 5.3.2 | Test conditions | 17 |
| 5.4 | Restrained flexible joints | 18 |
| 5.5 | Long term hydrostatic strength test | 21 |
| 5.5.1 | PE pipes | 21 |
| 5.5.2 | Pull out test at 25 °C for PE restrained joints | 21 |
| 5.5.3 | PVC pipes | 22 |
| 5.6 | Flanged joints | 22 |
| 6 | Test methods | 22 |
| 6.1 | Tensile testing | 22 |
| 6.1.1 | Samples | 22 |
| 6.1.2 | Preparation of test bar | 23 |
| 6.1.3 | Apparatus and test method | 23 |

| | | |
|---|---|----|
| 6.1.4 | Test results | 23 |
| 6.2 | Brinell hardness | 24 |
| 6.3 | Routine water tightness test | 24 |
| 6.3.1 | General | 24 |
| 6.3.2 | Air test | 24 |
| 6.3.3 | Hydrostatic pressure test | 24 |
| 7 | Performance tests | 24 |
| 7.1 | Positive internal pressure joint water tightness | 24 |
| 7.1.1 | Coupling | 24 |
| 7.1.2 | Flange adaptor | 25 |
| 7.2 | Negative internal pressure joint | 26 |
| 7.3 | Dynamic internal pressure joint water tightness | 26 |
| 7.4 | Long term hydrostatic strength test for joints for PE pipes | 27 |
| 7.4.1 | Test piece | 27 |
| 7.4.2 | Test procedure | 27 |
| 7.5 | Pull out test at 25 °C for restrained joints for PE pipes | 27 |
| 7.5.1 | Test assembly | 27 |
| 7.5.2 | Apparatus | 27 |
| 7.5.3 | Test procedure | 27 |
| 7.6 | Long term hydrostatic strength test for joints of fittings for PVC pipe | 28 |
| 7.6.1 | Test piece | 28 |
| 7.6.2 | Test procedure | 28 |
| Annex A (informative) Outside diameters of existing pipes | | 29 |
| Annex B (informative) Quality assurance | | 32 |
| B.1 | General | 32 |
| B.2 | Performance test | 32 |
| B.3 | Manufacturing process | 33 |
| Bibliography | | 34 |