

# ISO 23991:2022-04 (E)

## Irrigation applications of ductile iron pipelines - Product design and installation

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviated terms .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Piped network for irrigation applications .....</b>	<b>3</b>
<b>5</b>	<b>Technical requirements of DI pipeline components for irrigation applications .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Material characteristics .....</b>	<b>3</b>
<b>5.3</b>	<b>Pressure class and dimensions .....</b>	<b>4</b>
<b>5.3.1</b>	<b>Preferred pressure classes .....</b>	<b>4</b>
<b>5.3.2</b>	<b>Allowable pressures .....</b>	<b>4</b>
<b>5.3.3</b>	<b>Diameter of socket and spigot pipes .....</b>	<b>5</b>
<b>5.3.4</b>	<b>Length of Socket and spigot pipes .....</b>	<b>6</b>
<b>5.3.5</b>	<b>Dimensions of flanged pipes and fittings .....</b>	<b>7</b>
<b>5.4</b>	<b>Coating and lining for pipes .....</b>	<b>7</b>
<b>5.4.1</b>	<b>General .....</b>	<b>7</b>
<b>5.4.2</b>	<b>External coatings .....</b>	<b>7</b>
<b>5.4.3</b>	<b>Internal linings .....</b>	<b>7</b>
<b>5.5</b>	<b>Coatings and linings for fittings and accessories .....</b>	<b>8</b>
<b>5.6</b>	<b>Abrasion resistance of lining .....</b>	<b>8</b>
<b>5.7</b>	<b>Marking .....</b>	<b>8</b>
<b>5.8</b>	<b>Joints and leak tightness requirements .....</b>	<b>8</b>
<b>5.8.1</b>	<b>Flexible joints .....</b>	<b>8</b>
<b>5.8.2</b>	<b>Restrained joints .....</b>	<b>8</b>
<b>6</b>	<b>Valves, irrigation hydrant, water meter .....</b>	<b>9</b>
<b>7</b>	<b>Designing factors of DI pipeline components for irrigation applications .....</b>	<b>9</b>
<b>7.1</b>	<b>General .....</b>	<b>9</b>
<b>7.2</b>	<b>Pipe layout .....</b>	<b>9</b>
<b>7.3</b>	<b>PIN classification .....</b>	<b>9</b>
<b>7.4</b>	<b>Hydraulic design .....</b>	<b>10</b>
<b>7.4.1</b>	<b>Water demand .....</b>	<b>10</b>
<b>7.4.2</b>	<b>Diameter selection and head loss calculation .....</b>	<b>11</b>
<b>7.4.3</b>	<b>Flow velocity .....</b>	<b>13</b>
<b>7.5</b>	<b>Mechanical design .....</b>	<b>13</b>
<b>7.5.1</b>	<b>Pressure resistance .....</b>	<b>13</b>
<b>7.5.2</b>	<b>Deflection resistance .....</b>	<b>13</b>
<b>7.6</b>	<b>Protection against soil corrosiveness .....</b>	<b>14</b>
<b>7.6.1</b>	<b>General .....</b>	<b>14</b>
<b>7.6.2</b>	<b>Metallic zinc-based coatings .....</b>	<b>14</b>
<b>7.6.3</b>	<b>Alternative coatings .....</b>	<b>14</b>
<b>7.7</b>	<b>Protection against water aggressiveness .....</b>	<b>14</b>
<b>7.7.1</b>	<b>General .....</b>	<b>14</b>
<b>7.7.2</b>	<b>Cement lining .....</b>	<b>14</b>

<b>8</b>	<b>Laying DI pipeline components for irrigation applications .....</b>	<b>15</b>
8.1	laying calculations .....	15
8.2	laying operations .....	15
8.2.1	General .....	15
8.2.2	Layout .....	15
8.2.3	Handling .....	15
8.2.4	Laying in trench .....	15
<b>ISO 23991:2022(E) 8.2.5</b>	<b>Laying above ground .....</b>	<b>17</b>
8.2.6	Laying in slope .....	17
8.2.7	Laying in an open canal .....	18
8.2.8	Trenchless laying .....	19
8.3	Pipeline assembling .....	19
8.3.1	General .....	19
8.3.2	Advantages of flexible push-on joint in inconsistent or unstable ground .....	20
<b>9</b>	<b>Operation and total cost of ownership of a PIN .....</b>	<b>21</b>
9.1	Operation and maintenance .....	21
9.2	Life cycle cost analysis .....	21
9.3	Key parameters for life cycle cost .....	21
9.4	Circular economy .....	22
<b>Annex A (informative)</b>	<b>Advantages of piped irrigation networks .....</b>	<b>23</b>
<b>Annex B (informative)</b>	<b>Piped irrigation network planning .....</b>	<b>24</b>
<b>Annex C (informative)</b>	<b>Efficiency factor .....</b>	<b>27</b>
<b>Annex D (informative)</b>	<b>Push-in joints of DI pipes .....</b>	<b>28</b>
<b>Bibliography</b>	<b>.....</b>	<b>30</b>