

DIN EN 1253-8:2023-06 (E)

Gullies for buildings - Part 8: Trapped floor gullies with combined mechanical closure and water seal

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Design and construction | 8 |
| 4.1 | General | 8 |
| 4.2 | Appearance | 8 |
| 4.3 | Apertures in gratings | 8 |
| 4.4 | Resistance of trap with mechanical closure and water seal to pressure | 9 |
| 4.4.1 | Requirements | 9 |
| 4.4.2 | Test method | 9 |
| 4.5 | Blockage prevention | 10 |
| 4.5.1 | Access for cleaning | 10 |
| 4.5.2 | Clogging test | 11 |
| 4.6 | Places of installation | 13 |
| 4.7 | Materials | 13 |
| 4.8 | Thermal behaviour of floor gullies | 13 |
| 4.8.1 | General | 13 |
| 4.8.2 | Requirements | 13 |
| 4.8.3 | Test method | 13 |
| 4.8.4 | Additional test for floor gullies for use with sheet floor coverings and liquid applied membranes | 14 |
| 4.9 | Tightness | 15 |
| 4.9.1 | Odour-tightness | 15 |
| 4.9.2 | Watertightness of bodies | 16 |
| 4.9.3 | Watertightness of extensions | 16 |
| 4.10 | Mechanical strength | 17 |
| 4.10.1 | Loading strength | 17 |
| 4.10.2 | Clamping ring strength | 19 |
| 4.10.3 | Additional mechanical strength according to the installation | 20 |
| 4.10.4 | Floor gullies for use with liquid applied membranes | 23 |
| 4.11 | Flow rates | 23 |
| 4.11.1 | Requirements | 23 |
| 4.11.2 | Test method | 24 |
| 4.11.3 | Test arrangement | 24 |
| 5 | Allocation and sequence of tests | 25 |
| 6 | Marking | 27 |
| 7 | Evaluation of conformity | 27 |
| Annex A (normative) Examples of top view of the positioning of shape of test blocks applied on the gratings | | 28 |
| Annex B (normative) Test solutions | | 30 |
| Bibliography | | 32 |