

DIN EN 1253-8:2023-06 (E)

Gullies for buildings - Part 8: Trapped floor gullies with combined mechanical closure and water seal

Contents		Page
European foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Design and construction	8
4.1	General	8
4.2	Appearance	8
4.3	Apertures in gratings	8
4.4	Resistance of trap with mechanical closure and water seal to pressure	9
4.4.1	Requirements	9
4.4.2	Test method	9
4.5	Blockage prevention	10
4.5.1	Access for cleaning	10
4.5.2	Clogging test	11
4.6	Places of installation	13
4.7	Materials	13
4.8	Thermal behaviour of floor gullies	13
4.8.1	General	13
4.8.2	Requirements	13
4.8.3	Test method	13
4.8.4	Additional test for floor gullies for use with sheet floor coverings and liquid applied membranes	14
4.9	Tightness	15
4.9.1	Odour-tightness	15
4.9.2	Watertightness of bodies	16
4.9.3	Watertightness of extensions	16
4.10	Mechanical strength	17
4.10.1	Loading strength	17
4.10.2	Clamping ring strength	19
4.10.3	Additional mechanical strength according to the installation	20
4.10.4	Floor gullies for use with liquid applied membranes	23
4.11	Flow rates	23
4.11.1	Requirements	23
4.11.2	Test method	24
4.11.3	Test arrangement	24
5	Allocation and sequence of tests	25
6	Marking	27
7	Evaluation of conformity	27
Annex A (normative) Examples of top view of the positioning of shape of test blocks applied on the gratings		28
Annex B (normative) Test solutions		30
Bibliography		32