DIN 19643-3:2023-06 (E)

Treatment of water of swimming pools and baths - Part 3: Combinations of process with ozonization and chlorination

Contents

Page

Foreword 4

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Principles of the process combinations 7
4.1 General 7
4.2 Flocculation - Filtration - Ozonation - Sorption filtration - Chlorination 8
4.3 Flocculation - Ozonation - Multi-layer filtration with sorption - Chlorination 8

5 Process stages 9
5.1 Adjusting the acid neutralizing capacity 9
5.1.1 General 9
5.1.2 Reagents for adjusting the acid neutralizing capacity 9
5.1.3 Values for the acid neutralizing capacity of the raw water 9
5.1.4 Checking the acid neutralizing capacity 10
5.2 pH value adjustment 10
5.3 Flocculation 10
5.3.1 General 10
5.3.2 Flocculants 13
5.3.3 Minimum quantity of flocculant to be added 14
5.3.4 Checking the flocculant dosage 14
5.4 Ozonation 14
5.4.1 General 14
5.4.2 Ozone mass concentration 15
5.4.3 Ozone dosage and ozone reaction time 15
5.4.4 Checking the ozone generation system 16
5.5 Flocculation filtration in the process combination Flocculation - Filtration - Ozonation - Sorption filtration - Chlorination 16
5.5.1 General 16
5.5.3 Checking the filtration 21
5.6 Sorption filtration in the process combination Flocculation - Filtration - Ozonation - Sorption filtration - Chlorination 21
5.6.1 General 21
5.6.2 Particle size ranges, filter bed heights and filtration rates 22
5.6.3 Backwashing of sorption filters 22
5.6.4 Checking the filtration 24
5.7 Multi-layer filtration in the process combination Flocculation - Ozonation - Multi-layer filtration with sorption effect - Chlorination 24
5.7.1 General 24
5.7.2 Filter bed heights, particle size ranges and filtration rates 24
5.7.3 Backwashing multi-layer filters with sorption effect 25
5.7.4 Checking the filtration 28
5.8 Checking the flocculation filtration and sorption filtration 28
5.9 Chlorination 30
5.9.1 General 30
5.9.2 Chlorine concentration 30

6 Load capacity factor k 30

Annex A (informative) Simplified representation of process combinations (examples) 31

Bibliography 34

Figures

Figure 1 — Correlation between pipe internal diameter and flow rate 13

Figure A.1 — Simplified diagram of the process combination flocculation – filtration – ozonation – sorption filtration – chlorination 31

Figure A.2 — Simplified diagram of the process combination flocculation – ozonation – multi-layer filtration with sorption effect – chlorination (pressurized ozone reaction vessel) 32

Figure A.3 — Simplified diagram of the process combination flocculation – ozonation – multi-layer filtration with sorption effect – chlorination (ozone reaction vessel at atmospheric pressure) 33

Tables

Table 1 — Particle size ranges, filter bed heights and filtration rates for single-layer filters using silica sand 20

Table 2 — Particle size range combinations for multi-layer filters 20

Table 3 — Filter bed heights and filtration rates for multi-layer filters 21

Table 4 — Particle size ranges, filter bed heights and filtration rates for sorption filters 22

Table 5 — Particle size ranges, filter bed heights and filtration rates of multi-layer filters with sorption effect 25

Table 6 — Sample Backwashing programme for multi-layer filters with sorption effect as listed in Table 5 27

Table 7 — Specifications for checking filtration 28