ISO 24131-2:2023-03 (E)

Internal protection by polymeric lining for ductile iron pipes - Requirements and test methods - Part 2: Epoxy lining

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Technical requirements 3
4.1 General 3
4.2 Surface preparation 3
4.3 Lining appearance 4
4.4 Minimum lining thickness 4
4.5 Adhesion (pull off test/cross cut knife test) 4
4.6 Cross linkage (MIBK/Tg) 4
4.7 Non-porosity 4
4.8 Protection of pipe ends 4
4.9 Marking 5
4.10 Repairs 5

5 Performance requirements 5
5.1 General 5
5.2 Materials in contact with water intended for human consumption 5
5.3 Abrasion resistance only for sewage applications 5
5.4 Chemical resistance only for sewage applications 6
5.5 Impact resistance 6
5.6 Indirect impact resistance 6
5.7 Resistance to hot water 6
5.8 Resistance to ovalization 6

6 Test methods 6
6.1 Routine tests 6
6.1.1 Surface preparation 6
6.1.2 Lining appearance 6
6.1.3 Lining thickness 7
6.1.4 Adhesion 7
6.1.5 Cross linkage (MIBK/Tg) 7
6.1.6 Non-porosity 7
6.1.7 Marking 7
6.1.8 Repairs 7
6.2 Performance test 8
6.2.1 Abrasion resistance only for sewage applications 8
6.2.2 Chemical resistance only for sewage applications 8
6.2.3 Impact resistance 8
6.2.4 Indirect impact resistance 8
6.2.5 Resistance to hot water 8
6.2.6 Resistance to ovalization 8

Annex A (normative) Quality assurance 10

Annex B (normative) Cross cut knife test method 12

Annex C (informative) Handling, transportation and storage 13

Bibliography 14