

ISO 24131-2:2023-03 (E)

Internal protection by polymeric lining for ductile iron pipes - Requirements and test methods - Part 2: Epoxy lining

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Technical requirements	3
4.1	General	3
4.2	Surface preparation	3
4.3	Lining appearance	4
4.4	Minimum lining thickness	4
4.5	Adhesion (pull off test/cross cut knife test)	4
4.6	Cross linkage (MIBK/Tg)	4
4.7	Non-porosity	4
4.8	Protection of pipe ends	4
4.9	Marking	5
4.10	Repairs	5
5	Performance requirements	5
5.1	General	5
5.2	Materials in contact with water intended for human consumption	5
5.3	Abrasion resistance only for sewage applications	5
5.4	Chemical resistance only for sewage applications	6
5.5	Impact resistance	6
5.6	Indirect impact resistance	6
5.7	Resistance to hot water	6
5.8	Resistance to ovalization	6
6	Test methods	6
6.1	Routine tests	6
6.1.1	Surface preparation	6
6.1.2	Lining appearance	6
6.1.3	Lining thickness	7
6.1.4	Adhesion	7
6.1.5	Cross linkage (MIBK/Tg)	7
6.1.6	Non-porosity	7
6.1.7	Marking	7
6.1.8	Repairs	7
6.2	Performance test	8
6.2.1	Abrasion resistance only for sewage applications	8
6.2.2	Chemical resistance only for sewage applications	8
6.2.3	Impact resistance	8
6.2.4	Indirect impact resistance	8
6.2.5	Resistance to hot water	8
6.2.6	Resistance to ovalization	8
Annex A (normative)	Quality assurance	10
Annex B (normative)	Cross cut knife test method	12
Annex C (informative)	Handling, transportation and storage	13
Bibliography		14