

DIN EN 17694-2:2024-01 (E)

Hydrometry - Minimum performance requirements and test procedures for water monitoring equipment - Devices for the determination of flow - Part 2: Closed conduit instrumentation

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols | 8 |
| 5 | Principle | 9 |
| 6 | General requirements | 10 |
| 6.1 | Requirements for closed conduit instrumentation | 10 |
| 6.2 | Requirements for associated documentation | 11 |
| 7 | Performance requirements | 12 |
| 7.1 | Expression of performance requirements | 12 |
| 7.2 | Performance requirements | 13 |
| 7.3 | Data retention | 14 |
| 7.4 | Environmental requirements | 14 |
| 7.5 | Water temperature requirements | 14 |
| 7.6 | Installation influences | 14 |
| 7.7 | Field test requirements | 14 |
| 8 | Testing | 15 |
| 8.1 | General requirements for testing | 15 |
| 8.2 | Laboratory test conditions | 15 |
| 8.3 | Reporting | 17 |
| 9 | Laboratory test procedures | 17 |
| 9.1 | Guidance for establishing a test plan | 17 |
| 9.2 | Verification by inspection | 20 |
| 9.3 | Performance tests | 20 |
| 9.3.1 | Loss of power for electronic CCIs | 20 |
| 9.3.2 | Bias and repeatability | 20 |
| 9.3.3 | Supply voltage | 21 |
| 9.3.4 | Output impedance | 22 |
| 9.3.5 | Water temperature | 22 |
| 9.3.6 | Ambient air temperature and relative humidity | 22 |
| 9.3.7 | Sensor location | 23 |
| 9.3.8 | Presence of stray currents | 24 |
| 9.3.9 | Bi-directional flow | 25 |
| 9.3.10 | Flow reversal | 25 |
| 9.3.11 | Ancillary devices | 25 |
| 9.3.12 | Effect of conduit material | 26 |
| 9.3.13 | Effect of conduit size | 26 |

| | | |
|--|---|----|
| 9.3.14 | Fill level | 27 |
| 9.3.15 | Response time | 27 |
| 10 | Field test procedures | 28 |
| 10.1 | Objective of field test | 28 |
| 10.2 | Field test plan | 28 |
| 10.3 | Field test requirements | 28 |
| 10.4 | Error under field test conditions | 29 |
| 10.5 | Up-time | 29 |
| 10.6 | Maintenance | 30 |
| Annex A (normative) Evaluation of test data | | 31 |
| A.1 | Introduction | 31 |
| A.2 | Bias | 31 |
| A.3 | Repeatability | 32 |
| A.4 | Effect of influence quantities | 32 |
| A.5 | Combined performance requirement | 32 |
| A.6 | Worked example | 34 |
| A.6.1 | Bias | 34 |
| A.6.2 | Repeatability | 35 |
| A.6.3 | Influence conditions | 35 |
| A.7 | Worked example -- Field tests | 36 |
| Annex B (informative) Reference methods | | 40 |
| B.1 | Laboratory methods | 40 |
| B.2 | Field (in situ) methods | 40 |
| Annex C (informative) Reference uncertainty and error calculations | | 41 |
| Annex D (informative) Example report format | | 43 |
| Bibliography | | 46 |