

DIN EN 14944-3:2024-02 (E)

Influence of cementitious products on water intended for human consumption - Test methods - Part 3 : Migration of substances from factory-made cementitious products

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 8 |
| 4 | Principle | 10 |
| 5 | Reagents | 10 |
| 6 | Apparatus | 11 |
| 6.1 | General | 11 |
| 6.2 | Apparatus and materials for test piece preparation (see Annexes A, B and C) | 12 |
| 6.2.1 | Stainless steel plates and cylinders | 12 |
| 6.2.2 | Glass cylinders | 12 |
| 6.2.3 | Moulds for forming test pieces | 12 |
| 6.3 | Apparatus and materials for preconditioning and migration procedure | 12 |
| 7 | Samples and test pieces | 13 |
| 7.1 | Sampling, transport and storage of samples | 13 |
| 7.2 | Preparation of test pieces | 13 |
| 7.2.1 | General | 13 |
| 7.2.2 | Factory made pipes, fittings and storage systems | 13 |
| 7.3 | Surface area to volume ratio (S/V) for use in the test procedure | 14 |
| 7.3.1 | General | 14 |
| 7.3.2 | Pipes and fittings | 14 |
| 7.3.3 | Storage systems (cement mortar, cement mortar lined or concrete) | 14 |
| 8 | Pre-treatment of samples (curing and preconditioning) | 14 |
| 8.1 | General | 14 |
| 8.2 | Curing | 14 |
| 8.3 | Preconditioning | 15 |
| 9 | Test procedure | 15 |
| 9.1 | General | 15 |
| 9.2 | Preparation of migration water for analysis of substances | 15 |
| 9.2.1 | Introduction | 15 |
| 9.2.2 | Migration procedure | 15 |
| 9.2.3 | Second and third migration periods | 16 |
| 9.2.4 | Additional migration periods | 16 |
| 9.3 | Control samples (blank test) | 16 |
| 10 | Analysis | 16 |
| 11 | Calculation of test results | 16 |
| 11.1 | Calculation of the concentration of the substances in the migration water | 16 |
| 11.2 | Calculation of the migration rate of the measured substances | 17 |
| 11.3 | Calculation of the mean migration rate | 17 |

| | | |
|---|---|-----------|
| 12 | Test report | 17 |
| 12.1 | General | 17 |
| 12.2 | General information | 17 |
| 12.3 | Information on the product | 18 |
| 12.4 | Information on the test procedure | 18 |
| 12.5 | Test results | 19 |
| Annex A (normative) Additional procedures for testing factory-made pipes (cement mortar lined and concrete) | | 20 |
| A.1 | Sampling, test piece preparation and storage | 20 |
| A.1.1 | Sampling | 20 |
| A.1.2 | Test piece preparation and storage | 20 |
| A.2 | Surface area to volume (S/V) ratio | 24 |
| A.3 | Preconditioning of test pieces | 24 |
| A.4 | Test procedure | 24 |
| A.4.1 | Migration procedure at 23 °C | 24 |
| A.4.2 | Migration procedure at elevated temperature | 24 |
| A.5 | Expression of results | 24 |
| A.6 | Reporting | 24 |
| Annex B (normative) Additional procedures for testing factory made fittings (cement mortar lined and concrete) | | 25 |
| B.1 | Sampling, test piece preparation and storage | 25 |
| B.1.1 | Sampling of factory-made fittings | 25 |
| B.1.2 | Test piece preparation and storage | 25 |
| B.2 | Surface area to volume (S/V) ratio | 29 |
| B.3 | Preconditioning of test pieces | 29 |
| B.4 | Test procedure | 29 |
| B.4.1 | Migration procedure at 23 °C | 29 |
| B.4.2 | Migration procedure at elevated temperature | 29 |
| B.5 | Expression of results | 29 |
| B.6 | Reporting | 29 |
| Annex C (normative) Additional procedures for testing factory-made storage systems (cement mortar, cement mortar lined and concrete) | | 30 |
| C.1 | Sampling, test piece preparation and storage | 30 |
| C.1.1 | Sampling | 30 |
| C.1.2 | Test piece preparation and storage | 30 |
| C.2 | Surface area to volume (S/V) ratio | 34 |
| C.3 | Preconditioning of test pieces | 34 |
| C.4 | Test procedure | 34 |
| C.4.1 | Migration procedure at 23 °C | 34 |
| C.4.2 | Migration procedure at elevated temperature | 34 |
| C.5 | Expression of results | 34 |
| C.6 | Reporting | 34 |
| Annex D (informative) Examples of typical test pieces and test conditions as a function of S/V ratio | | 35 |
| D.1 | General | 35 |
| D.2 | Pipes and fittings | 35 |
| D.3 | Test pieces to which a cylinder of stainless steel or glass is to be attached | 36 |
| D.4 | Square test plates coated with mortar | 37 |
| D.5 | Moulded test pieces where all faces are exposed to test water | 37 |
| Annex E (informative) Test arrangements for testing factory-made cement-based products | | 40 |
| Annex F (normative) Additional procedures for testing factory-made cement based products at elevated temperature | | 47 |

| | | |
|---|---|-----------|
| F.1 | General | 47 |
| F.2 | Test procedure at elevated temperature | 47 |
| F.2.1 | General | 47 |
| F.2.2 | Preparation of migration water for analysis of substances | 47 |
| F.3 | Control samples (blank test) | 47 |
| F.4 | Expression of results | 47 |
| F.5 | Reporting | 48 |
| Annex G (informative) Discrimination between porous and non-porous coatings on factory-made products | | 49 |
| G.1 | Principle | 49 |
| G.2 | Apparatus | 49 |
| G.3 | Materials and reagents | 49 |
| G.4 | Test procedure | 49 |
| G.4.1 | General | 49 |
| G.4.2 | Laboratory blank | 49 |
| G.4.3 | Coated product | 50 |
| G.5 | Determination of pH | 50 |
| G.6 | Expression of results | 50 |
| G.7 | Classification criteria | 51 |
| Annex H (informative) Schematic description of the test procedure | | 52 |
| H.1 | Preconditioning | 52 |
| H.2 | Production of migration water at 23 °C | 53 |
| H.3 | Typical Schedule | 54 |
| H.3.1 | Preconditioning | 54 |
| H.3.2 | Production of migration waters | 54 |
| Annex I (informative) Procedural tests using standard additions (positive controls) | | 55 |
| Bibliography | | 56 |