

# DIN EN ISO 18475:2026-02 (E)

## Environmental solid matrices - Determination of polychlorinated biphenyls (PCB) by gas chromatography - mass selective detection (GC-MS) or electron-capture detection (GC-ECD) (ISO 18475:2023)

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>		<b>v</b>
<b>Introduction</b>		<b>vii</b>
<b>1 Scope</b>		<b>1</b>
<b>2 Normative references</b>		<b>1</b>
<b>3 Terms and definitions</b>		<b>2</b>
<b>4 Principle</b>		<b>3</b>
<b>5 Interferences</b>		<b>4</b>
5.1	Interference with sampling and extraction	4
5.2	Interference with GC	4
<b>6 Safety remarks</b>		<b>5</b>
<b>7 Reagents</b>		<b>5</b>
7.1	General	5
7.2	Reagents for extraction	5
7.3	Reagents for clean-up	5
7.3.1	Clean-up A using aluminium oxide	5
7.3.2	Clean-up B using silica gel 60 for column chromatography	6
7.3.3	Clean-up C using gel permeation chromatography (GPC)	6
7.3.4	Clean-up D using Florisil®	6
7.3.5	Clean-up E using silica H <sub>2</sub> SO <sub>4</sub> /silica NaOH	7
7.3.6	Clean-up F using benzenesulfonic acid/sulfuric acid	7
7.3.7	Clean-up G using TBA sulfite reagent	7
7.3.8	Clean-up H using pyrogenic copper	7
7.3.9	Clean-up I using silica/silver nitrate	8
7.4	Gas chromatographic analysis	8
7.5	Standards	9
7.5.1	General	9
7.5.2	Calibration standards	9
7.5.3	Internal and injection standards	9
7.6	Preparation of standard solutions	10
7.6.1	Preparation of calibration standard solutions of PCBs	10
7.6.2	Preparation of internal standard solution	11
7.6.3	Preparation of injection standard solution	11
<b>8 Apparatus</b>		<b>11</b>
8.1	Extraction and clean-up procedures	11
8.2	Gas chromatograph	12
<b>9 Sample storage and preservation</b>		<b>12</b>
9.1	Sample storage	12
9.2	Sample pre-treatment	13
<b>10 Procedure</b>		<b>13</b>
10.1	Blank test	13
10.2	Extraction	13
10.2.1	General	13
10.2.2	Extraction procedure 1: Samples using acetone/petroleum ether or hexane-like solvent and agitation or sonication	14
10.2.3	Extraction procedure 2: Samples using Soxhlet or pressurized liquid extraction	15

10.2.4	Extraction procedure 3: Samples using acetone/petroleum ether or hexane-like solvent/sodium chloride and agitation.....	15
10.3	Concentration.....	16
10.4	Clean-up of the extract.....	16
10.4.1	General.....	16
10.4.2	Clean-up A – Aluminium oxide.....	17
10.4.3	Clean-up B – Silica gel.....	17
10.4.4	Clean-up C – Gel permeation chromatography.....	17
10.4.5	Clean-up D – Florisil®.....	18
10.4.6	Clean-up E – Silica H <sub>2</sub> SO <sub>4</sub> /silica NaOH.....	18
10.4.7	Clean-up F – Benzenesulfonic acid/sulfuric acid.....	18
10.4.8	Clean-up G – TBA sulfite reagent.....	19
10.4.9	Clean-up H – Clean-up using pyrogenic copper to remove elemental sulfur and some other organic sulfur compounds.....	19
10.4.10	Clean up I – AgNO <sub>3</sub> /silica.....	19
10.5	Addition of the injection standard.....	19
10.6	Gas chromatographic analysis (GC).....	19
10.6.1	General.....	19
10.6.2	Setting the gas chromatograph.....	19
10.7	Mass spectrometry (MS).....	20
10.7.1	Mass spectrometric conditions.....	20
10.7.2	Calibration of the method using an internal standard.....	20
10.7.3	Measurement.....	21
10.7.4	Identification.....	22
10.7.5	Check on method performance.....	22
10.7.6	Calculation.....	23
10.8	Electron capture detection (ECD).....	24
10.8.1	General.....	24
10.8.2	ECD conditions.....	24
10.8.3	Calibration of the method using internal standards.....	24
10.8.4	Measurement.....	24
10.8.5	Identification.....	24
10.8.6	Check on ECD method performance.....	24
10.8.7	Calculation.....	25
<b>11</b>	<b>Performance characteristics.....</b>	<b>25</b>
<b>12</b>	<b>Precision.....</b>	<b>25</b>
<b>13</b>	<b>Test report.....</b>	<b>26</b>
<b>Annex A</b>	<b>(informative) Repeatability and reproducibility data.....</b>	<b>27</b>
<b>Annex B</b>	<b>(informative) Examples for gas chromatographic conditions and retention times of PCBs.....</b>	<b>32</b>
<b>Annex C</b>	<b>(informative) Calculation method for the estimation of total PCB content.....</b>	<b>33</b>
<b>Bibliography</b>	<b>.....</b>	<b>40</b>