DIN EN 13476-2:2026-06 (E)

Plastics piping systems for non-pressure underground drains and sewers - Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) - Part 2: Specifications for pipes and fittings with smooth internal and external surface and the system, Type A

Contents

Page

European foreword 5

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions 10

4 Symbols and abbreviations 11
4.1 Symbols 11
4.2 Abbreviations 11

5 Material 12
5.1 General 12
5.2 Unplasticized poly(vinyl chloride) (PVC-U) 12
5.2.1 General 12
5.2.2 Formulation characteristics of pipe and fitting 13
5.3 Polypropylene (PP) 13
5.3.1 General 13
5.3.2 Compound characteristics for pipe and fitting 14
5.3.3 Melt mass-flow rate classification 15
5.4 Polyethylene (PE) 16
5.4.1 General 16
5.4.2 Compound characteristics of pipe and injection moulded fittings 16
5.4.3 Compound characteristics of rotational-moulded fittings 18
5.5 Sealing ring retaining components 19
5.6 Sealing rings 19
5.7 Fused or welded joints 19
5.8 Adhesives for PVC-U 19

6 Designation of wall constructions and examples of typical jointing methods 19
6.1 General 19
6.2 Wall constructions designated as Type A 19
6.2.1 Multilayer construction or hollow-wall construction with axial hollow sections, Type A1 19
6.2.2 Hollow-wall construction with spirally or radial formed hollow sections, Type A2 20
6.2.3 Typical jointing methods for structured-wall pipes Type A 21
6.3 Designation and design of joints 22

7 Appearance and colour 22

8 Geometrical characteristics 22
8.1 General 22
8.2 Dimensions 22
8.2.1 Designation 22
8.2.2 Lengths of pipe 22
8.2.3 Diameters of Type A pipes and Type A spigots of pipes and fittings 23

8.2.4 Diameters and jointing dimensions of sockets and spigots 26
8.2.5 Wall thicknesses 27
8.3 Types of fittings 29
8.4 Design length of fittings 29

9 Physical characteristics 29
9.1 Unplasticized poly(vinyl chloride) (PVC-U) 29
9.1.1 Physical characteristics of PVC-U pipes 29
9.1.2 Physical characteristics of PVC-U fittings 30
9.2 Polypropylene (PP) 31
9.2.1 Physical characteristics of PP pipes 31
9.2.2 Physical characteristics of PP fittings 32
9.3 Polyethylene (PE) 32
9.3.1 Physical characteristics of PE pipes 32
9.3.2 Physical characteristics of PE fittings 32

10 Mechanical characteristics 33
10.1 Mechanical characteristics of pipes 33
10.1.1 General requirements 33
10.1.2 Ring flexibility 35
10.1.3 Tensile strength of seams (Type A.2) 35
10.2 Mechanical characteristics of fittings 35

11 Performance requirements 37

12 Marking 39
12.1 General 39
12.2 Minimum required marking 39
12.2.1 Pipes 39
12.2.2 Fittings 40
12.3 Additional marking 41
12.3.1 General 41

Annex A (normative) Formulation PVC-U material 42

Annex B (normative) Utilization of PVC-U recyclates 43

B.1 General 43
B.2 Agreed specification 43
B.3 Additional specifications for recyclate and agreed specifications 44

Annex C (normative) Compound PP material 46

Annex D (normative) Utilization of PP recyclate 47

D.1 General 47
D.2 Agreed specification 47
D.3 Additional specifications for recyclate and agreed specification 48

Annex E (normative) Compound PE material 49

Annex F (normative) Utilization of PE recyclate 51

F.1 General 51
F.2 Agreed specification 51
F.3 Additional specifications for recyclate and agreed specification 52

Annex G (normative) Impact test at 23 °C 54

Annex H (normative) Impact test at -10 °C 55

Annex I (normative) Ring flexibility test at 20 % diametric deflection 56

Annex J (normative) Impact test for large diameter pipes with structured wall 57

J.1 Principle 57
J.2 Apparatus 57
J.3 Test samples 58
J.3.1 Preparation 58
J.3.2 Number of test pieces 58
J.4 Conditioning 58
J.5 Procedure 58
J.6 Test result 60

Bibliography 61