

DIN EN 13476-2:2026-06 (E)

Plastics piping systems for non-pressure underground drains and sewers -
Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U),
polypropylene (PP) and polyethylene (PE) - Part 2: Specifications for pipes and
fittings with smooth internal and external surface and the system, Type A

Contents		Page
European foreword		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	10
4	Symbols and abbreviations	11
4.1	Symbols	11
4.2	Abbreviations	11
5	Material	12
5.1	General	12
5.2	Unplasticized poly(vinyl chloride) (PVC-U)	12
5.2.1	General	12
5.2.2	Formulation characteristics of pipe and fitting	13
5.3	Polypropylene (PP)	13
5.3.1	General	13
5.3.2	Compound characteristics for pipe and fitting	14
5.3.3	Melt mass-flow rate classification	15
5.4	Polyethylene (PE)	16
5.4.1	General	16
5.4.2	Compound characteristics of pipe and injection moulded fittings	16
5.4.3	Compound characteristics of rotational-moulded fittings	18
5.5	Sealing ring retaining components	19
5.6	Sealing rings	19
5.7	Fused or welded joints	19
5.8	Adhesives for PVC-U	19
6	Designation of wall constructions and examples of typical jointing methods	19
6.1	General	19
6.2	Wall constructions designated as Type A	19
6.2.1	Multilayer construction or hollow-wall construction with axial hollow sections, Type A1 ..	19
6.2.2	Hollow-wall construction with spirally or radial formed hollow sections, Type A2	20
6.2.3	Typical jointing methods for structured-wall pipes Type A	21
6.3	Designation and design of joints	22
7	Appearance and colour	22
8	Geometrical characteristics	22
8.1	General	22
8.2	Dimensions	22
8.2.1	Designation	22
8.2.2	Lengths of pipe	22
8.2.3	Diameters of Type A pipes and Type A spigots of pipes and fittings	23

8.2.4	Diameters and jointing dimensions of sockets and spigots	26
8.2.5	Wall thicknesses	27
8.3	Types of fittings	29
8.4	Design length of fittings	29
9	Physical characteristics	29
9.1	Unplasticized poly(vinyl chloride) (PVC-U)	29
9.1.1	Physical characteristics of PVC-U pipes	29
9.1.2	Physical characteristics of PVC-U fittings	30
9.2	Polypropylene (PP)	31
9.2.1	Physical characteristics of PP pipes	31
9.2.2	Physical characteristics of PP fittings	32
9.3	Polyethylene (PE)	32
9.3.1	Physical characteristics of PE pipes	32
9.3.2	Physical characteristics of PE fittings	32
10	Mechanical characteristics	33
10.1	Mechanical characteristics of pipes	33
10.1.1	General requirements	33
10.1.2	Ring flexibility	35
10.1.3	Tensile strength of seams (Type A.2)	35
10.2	Mechanical characteristics of fittings	35
11	Performance requirements	37
12	Marking	39
12.1	General	39
12.2	Minimum required marking	39
12.2.1	Pipes	39
12.2.2	Fittings	40
12.3	Additional marking	41
12.3.1	General	41
Annex A	(normative) Formulation PVC-U material	42
Annex B	(normative) Utilization of PVC-U recyclates	43
B.1	General	43
B.2	Agreed specification	43
B.3	Additional specifications for recyclate and agreed specifications	44
Annex C	(normative) Compound PP material	46
Annex D	(normative) Utilization of PP recyclate	47
D.1	General	47
D.2	Agreed specification	47
D.3	Additional specifications for recyclate and agreed specification	48
Annex E	(normative) Compound PE material	49
Annex F	(normative) Utilization of PE recyclate	51
F.1	General	51
F.2	Agreed specification	51
F.3	Additional specifications for recyclate and agreed specification	52
Annex G	(normative) Impact test at 23 °C	54
Annex H	(normative) Impact test at -10 °C	55
Annex I	(normative) Ring flexibility test at 20 % diametric deflection	56

Annex J (normative) Impact test for large diameter pipes with structured wall	57
J.1 Principle	57
J.2 Apparatus	57
J.3 Test samples	58
J.3.1 Preparation	58
J.3.2 Number of test pieces	58
J.4 Conditioning	58
J.5 Procedure	58
J.6 Test result	60
Bibliography	61