

DIN EN 15542:2026-05 (E)

Ductile iron pipes, fittings and accessories - External cement mortar coating for pipes - Requirements and test methods

| Contents | | Page |
|---|--|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 Scope | | 6 |
| 2 Normative references | | 6 |
| 3 Terms and definitions | | 7 |
| 4 Ordering information | | 8 |
| 5 Technical requirements | | 9 |
| 5.1 Zinc or zinc alloy coating | | 9 |
| 5.2 Fresh cement mortar layer thickness | | 9 |
| 5.3 Pipe ends | | 9 |
| 5.4 Appearance of cured cement mortar coating | | 9 |
| 5.5 Thickness of cured cement mortar coating | | 9 |
| 5.6 Repairs | | 9 |
| 5.7 Marking | | 9 |
| 6 Performance requirements | | 10 |
| 6.1 Cement mortar constituents | | 10 |
| 6.1.1 General | | 10 |
| 6.1.2 Cement | | 10 |
| 6.1.3 Aggregates | | 10 |
| 6.1.4 Fibres | | 10 |
| 6.1.5 Surface tissue | | 10 |
| 6.1.6 Saponification resistance of organic additives | | 10 |
| 6.2 Adhesion | | 10 |
| 6.3 Impact resistance | | 10 |
| 6.4 Specific pore transition resistance of the intermediate layer | | 11 |
| 7 Test methods | | 11 |
| 7.1 Routine tests | | 11 |
| 7.1.1 General | | 11 |
| 7.1.2 Zinc or zinc alloy coating | | 11 |
| 7.1.3 Thickness of the cement mortar layer | | 11 |
| 7.1.4 Pipe ends | | 11 |
| 7.1.5 Appearance and continuity of cured cement mortar coating | | 11 |
| 7.1.6 Thickness of the cured cement mortar coating | | 11 |
| 7.1.7 Repairs | | 11 |
| 7.1.8 Marking | | 11 |
| 7.2 Performance tests | | 11 |
| 7.2.1 General | | 11 |
| 7.2.2 Constituents | | 12 |
| 7.2.3 Adhesion | | 12 |
| 7.2.4 Impact strength | | 12 |
| 7.2.5 Specific pore transition resistance of the intermediate layer | | 13 |
| Annex A (informative) Quality assurance | | 16 |
| Annex B (informative) Application process | | 18 |
| Annex C (informative) Experiences from field and investigation | | 19 |
| Bibliography | | 20 |