

DIN EN 14364:2006-07 (E)

Plastics piping systems for drainage and sewerage with or without pressure - Glass-reinforced thermosetting plastics (GRP) based on unsaturated polyester resin (UP) - Specifications for pipes, fittings and joints

Contents		Page
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	8
3	Terms, definitions and symbols	9
4	General requirements	17
4.1	Classification	17
4.1.1	Categories	17
4.1.2	Nominal size	17
4.1.3	Nominal stiffness	17
4.1.4	Nominal pressure	17
4.2	Materials	18
4.2.1	General	18
4.2.2	Reinforcement	18
4.2.3	Resin	18
4.2.4	Aggregates and fillers	18
4.2.5	Elastomers	19
4.2.6	Metals	19
4.3	Wall construction	19
4.3.1	Inner layer	19
4.3.2	Structural layer	19
4.3.3	Outer layer	19
4.4	Appearance	19
4.5	Reference conditions for testing	20
4.5.1	Temperature	20
4.5.2	Properties of water for testing	20
4.5.3	Loading conditions	20
4.5.4	Preconditioning	20
4.5.5	Measurement of dimensions	20
4.6	Elapsed time for determination of long-term properties, (x)	20
4.7	Joints	20
4.7.1	General	20
4.7.2	Types of joint	20
4.7.3	Flexibility of the jointing system	20
4.7.4	Sealing ring	21
4.7.5	Adhesives	21
5	Pipes	21
5.1	Geometrical characteristics	21
5.1.1	Diameter	21
5.1.2	Wall thickness	25
5.1.3	Length	26
5.2	Mechanical characteristics	27
5.2.1	Initial specific ring stiffness	27

5.2.2	Long-term specific ring stiffness under wet conditions	28
5.2.3	Initial resistance to failure in a deflected condition	29
5.2.4	Ultimate long-term resistance to failure in a deflected condition	31
5.2.5	Initial specific longitudinal tensile strength	32
5.2.6	Initial failure and design pressures for pressure pipes	34
5.2.7	Long-term failure pressure	36
5.2.8	Resistance to strain corrosion	37
5.3	Marking	40
6	Fittings	40
6.1	General	40
6.1.1	Diameter series	40
6.1.2	Nominal pressure (PN)	40
6.1.3	Nominal stiffness (SN)	40
6.1.4	Joint type	41
6.1.5	Pipe type	41
6.1.6	Mechanical characteristics of fittings	41
6.1.7	Installed leak-tightness of fittings	41
6.1.8	Dimensions	41
6.2	Bends	41
6.2.1	Classification of bends	41
6.2.2	Dimensions and tolerances of bends	42
6.3	Branches	46
6.3.1	Classification of branches	46
6.3.2	Dimensions and tolerances of branches	46
6.4	Reducers	50
6.4.1	Classification of reducers	50
6.4.2	Dimensions and tolerances of reducers	50
6.4.3	Mechanical characteristics of tapered section laminate	53
6.5	Saddles	54
6.5.1	Classification of saddles	54
6.5.2	Dimensions and tolerances of saddles	55
6.6	Flanged adaptors	55
6.6.1	Classification of flanged adaptors	55
6.6.2	Dimensions and tolerances of flanged adaptors	56
6.7	Marking	57
7	Joint performance	58
7.1	General	58
7.1.1	Interchangeability	58
7.1.2	Test temperature	58
7.2	Dimensions	58
7.3	Non-end-load-bearing flexible joints with elastomeric sealing rings	58
7.3.1	General	58
7.3.2	Requirements	58
7.3.3	Number of test pieces for type test purposes	59
7.3.4	Test pieces	59
7.4	End-load-bearing flexible joints with elastomeric sealing rings	60
7.4.1	General	60
7.4.2	Performance requirements for locked-socket-and-spigot joints with elastomeric sealing rings	62
7.5	60 7.5 Wrapped or cemented joints	62
7.5.1	General	62
7.5.2	Performance requirements	62
7.5.3	Number of test pieces for type test purposes	63
7.5.4	Test pieces	63
7.6	Bolted flange joints	64
7.6.1	General	64
7.6.2	Performance requirements	64
7.6.3	Number of test pieces for type test purposes	65
7.6.4	Test pieces	65
7.6.5	Joint assembly details	65
7.6.6	Torque resistance	65

Annex A (normative) Test method for the resistance to bending and pressure of end-thrust loaded joints in pipe systems	67
A.1 Principle	67
A.2 Apparatus	67
A.3 Test pieces	67
A.4 Test temperature	68
A.5 Calculation of the bending load F	68
A.5.1 General	68
A.5.2 Calculation of F, if applied in the horizontal plane	68
A.5.3 Calculation of F, if applied in the vertical plane	68
A.6 Procedure	70
A.7 Test report	70
Bibliography	71