

# DIN EN 14897:2006-09 (E)

## Water conditioning equipment inside buildings - Devices using mercury low-pressure ultraviolet radiators - Requirements for performance, safety and testing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Definitions .....	4
4	Requirements .....	7
4.1	General .....	7
4.2	Radiation chamber .....	7
4.3	Low-pressure mercury UV lamps .....	7
4.4	Electrical .....	7
4.4.1	General .....	7
4.4.2	UV disinfection devices .....	7
4.4.3	UV bactericidal treatment devices .....	8
4.5	Performance .....	8
4.6	Labelling .....	8
4.7	Manual .....	9
5	Testing .....	9
5.1	General .....	9
5.2	Test rig and installation .....	10
5.3	Biosimetric measurements .....	10
5.4	Performance test procedure .....	11
5.4.1	UV disinfection devices .....	11
5.4.2	Processing of the data .....	13
5.4.3	UV bactericidal treatment devices .....	15
5.4.4	Processing of the data .....	15
Annex A (normative)	Requirements for the device sensor .....	17
A.1	Calibration .....	17
A.2	Selectivity .....	17
A.3	Measuring range linearity .....	17
A.4	Measuring range and resolution .....	17
A.5	Temperature drift .....	18
A.6	Stability over time .....	18
Annex B (normative)	Biosimulator calibration .....	19
Annex C (informative)	Monitoring window .....	22
Annex D (normative)	Manufacturer's information for the type test .....	23
Annex E (normative)	Manufacturer's information for the UV device user .....	25
Bibliography .....		26