

# DIN EN 15334:2007-05 (E)

## Sanitary appliances - Methacrylic dispersions of high filler content

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and Definitions .....</b>	<b>4</b>
<b>4</b>	<b>Characteristics of dispersion .....</b>	<b>5</b>
<b>5</b>	<b>Test methods .....</b>	<b>5</b>
<b>5.1</b>	<b>Tests on dispersion .....</b>	<b>5</b>
<b>5.1.1</b>	<b>Ash content .....</b>	<b>5</b>
<b>5.1.2</b>	<b>Agglomeration .....</b>	<b>6</b>
<b>5.1.3</b>	<b>Contamination .....</b>	<b>7</b>
<b>5.1.4</b>	<b>Density .....</b>	<b>7</b>
<b>5.1.5</b>	<b>Viscosity .....</b>	<b>8</b>
<b>5.1.6</b>	<b>Shrinkage during curing .....</b>	<b>10</b>
<b>5.2</b>	<b>Tests on finished part .....</b>	<b>11</b>
<b>5.2.1</b>	<b>General .....</b>	<b>11</b>
<b>5.2.2</b>	<b>Water absorption .....</b>	<b>11</b>
<b>5.2.3</b>	<b>Impact strength .....</b>	<b>11</b>
<b>5.2.4</b>	<b>Flexural modulus and flexural strength .....</b>	<b>11</b>
<b>5.2.5</b>	<b>Abrasion resistance .....</b>	<b>11</b>
<b>5.2.6</b>	<b>Scratch resistance .....</b>	<b>11</b>
<b>5.2.7</b>	<b>Barcol hardness .....</b>	<b>11</b>
<b>5.2.8</b>	<b>Vicat softening point .....</b>	<b>12</b>
<b>5.2.9</b>	<b>Resistance to chemical agents .....</b>	<b>12</b>
<b>5.2.10</b>	<b>UV resistance .....</b>	<b>13</b>
<b>5.2.11</b>	<b>Thermal expansion .....</b>	<b>13</b>
<b>Bibliography .....</b>		<b>14</b>