

DIN EN 14897:2007-09 (E)

Water conditioning equipment inside buildings - Devices using mercury low-pressure ultraviolet radiators - Requirements for performance, safety and testing (includes Amendment A1:2007)

| Contents | | Page |
|---|---|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Definitions | 4 |
| 4 | Requirements | 7 |
| 4.1 | General | 7 |
| 4.2 | Radiation chamber | 7 |
| 4.3 | Low-pressure mercury UV lamps | 7 |
| 4.4 | Electrical | 7 |
| 4.4.1 | General | 7 |
| 4.4.2 | UV disinfection devices | 7 |
| 4.4.3 | UV bactericidal treatment devices | 8 |
| 4.5 | Performance | 8 |
| 4.6 | Labelling | 8 |
| 4.7 | Manual | 9 |
| 5 | Testing | 9 |
| 5.1 | General | 9 |
| 5.2 | Test rig and installation | 10 |
| 5.3 | Biodosimetric measurements | 10 |
| 5.4 | Performance test procedure | 11 |
| 5.4.1 | UV disinfection devices | 11 |
| 5.4.2 | Processing of the data | 13 |
| 5.4.3 | UV bactericidal treatment devices | 15 |
| 5.4.4 | Processing of the data | 15 |
| Annex A (normative) Requirements for the device sensor | | 17 |
| A.1 | Calibration | 17 |
| A.2 | Selectivity | 17 |
| A.3 | Measuring range linearity | 17 |
| A.4 | Measuring range and resolution | 17 |
| A.5 | Temperature drift | 18 |
| A.6 | Stability over time | 18 |
| Annex B (normative) Biodosimeter calibration | | 19 |
| Annex C (informative) Monitoring window | | 22 |
| Annex D (normative) Manufacturer's information for the type test | | 23 |
| Annex E (normative) Manufacturer's information for the UV device user | | 25 |
| Annex F (normative) !Installation, operation and maintenance | | 26 |
| Bibliography | | 30 |