

# ISO 12301:2007-10 (E)

## Plain bearings - Quality control techniques and inspection of geometrical and material quality characteristics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Symbols and units .....</b>	<b>4</b>
<b>5</b>	<b>Summary of defined quality characteristics .....</b>	<b>5</b>
<b>6</b>	<b>Geometrical quality characteristics .....</b>	<b>7</b>
6.1	Wall thickness, $s_3$ .....	7
6.2	Outside diameter, $D_o$ .....	13
6.3	Inside diameter, $D_i$ .....	14
6.4	Width, $B$ .....	17
6.5	Locating features .....	18
6.6	Lubricant feed and distribution features .....	19
6.7	Surface conditions .....	20
6.8	Crush height, $a$ (peripheral length) .....	21
6.9	Free spread .....	22
6.10	Straightness of sliding surface .....	23
6.11	Joint face taper, $h$ .....	24
6.12	Back contact .....	24
6.13	Joint displacement, $B$ .....	25
6.14	Height of thrust half-washer, $H$ .....	25
6.15	Flatness .....	26
6.16	Flange diameter, $D_{fl}$ .....	27
6.17	Distance between flanges, $a_{fl}$ .....	28
6.18	Flange thickness, $s_{fl}$ .....	29
6.19	Perpendicularity (squareness) of flange .....	30
6.20	Geometric deviations .....	31
<b>7</b>	<b>Material quality characteristics .....</b>	<b>35</b>
7.1	Metallic solid materials .....	35
7.2	Metallic multilayer material .....	36
7.3	Polymer layer material .....	38
7.4	Solid polymer material .....	39
7.5	Sintered material .....	39
<b>Annex A (informative) Calculation of tangential load .....</b>		<b>40</b>
<b>Bibliography .....</b>		<b>47</b>