ISO 12130-2:2013-09 (E)

Plain bearings - Hydrodynamic plain tilting pad thrust bearings under steady-state conditions - Part 2: Functions for calculation of tilting pad thrust bearings

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative reference **1**

3 Functions for the tilting pad thrust bearing **1**

3.1 General 1

3.2 Characteristic value of load-carrying capacity, F^*, as a function of the relative bearing width, B/L, and the relative minimum lubricant film thickness, h_{min}/C_{wed} 1

3.3 Characteristic value of friction, f^*, as a function of the relative bearing width, B/L, and the relative minimum lubricant film thickness, h_{min}/C_{wed} 4

3.4 Relative lubricant flow rates Q_1^* and Q_3^* as a function of the relative bearing width, B/L, and the relative minimum lubricant film thickness, h_{min}/C_{wed} 5

3.5 Relative pressure centre coordinate or tilting pad supporting point a_F^* as a function of the relative bearing width, B/L, and the relative minimum lubricant film thickness, h_{min}/C_{wed} 8

4 Effective dynamic viscosity of the lubricant, η_{eff}, as a function of the effective lubricant film temperature, T_{eff} **10**

Bibliography **12**