

ISO 12130-2:2013-09 (E)

Plain bearings - Hydrodynamic plain tilting pad thrust bearings under steady-state conditions - Part 2: Functions for calculation of tilting pad thrust bearings

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative reference		1
3 Functions for the tilting pad thrust bearing		1
3.1 General.....		1
3.2 Characteristic value of load-carrying capacity, F^* , as a function of the relative bearing width, B/L , and the relative minimum lubricant film thickness, h_{\min}/C_{wed}		1
3.3 Characteristic value of friction, f^* , as a function of the relative bearing width, B/L , and the relative minimum lubricant film thickness, h_{\min}/C_{wed}		4
3.4 Relative lubricant flow rates Q_1^* and Q_3^* as a function of the relative bearing width, B/L , and the relative minimum lubricant film thickness, h_{\min}/C_{wed}		5
3.5 Relative pressure centre coordinate or tilting pad supporting point a_F^* as a function of the relative bearing width, B/L , and the relative minimum lubricant film thickness, h_{\min}/C_{wed}		8
4 Effective dynamic viscosity of the lubricant, η_{eff}, as a function of the effective lubricant film temperature, T_{eff}		10
Bibliography		12