

# ISO 12130-2:2013-09 (E)

## Plain bearings - Hydrodynamic plain tilting pad thrust bearings under steady-state conditions - Part 2: Functions for calculation of tilting pad thrust bearings

---

<b>Contents</b>		Page
<b>Foreword</b> .....		<b>iv</b>
<b>Introduction</b> .....		<b>v</b>
<b>1 Scope</b> .....		<b>1</b>
<b>2 Normative reference</b> .....		<b>1</b>
<b>3 Functions for the tilting pad thrust bearing</b> .....		<b>1</b>
3.1 General.....		1
3.2 Characteristic value of load-carrying capacity, $F^*$ , as a function of the relative bearing width, $B/L$ , and the relative minimum lubricant film thickness, $h_{\min}/C_{\text{wed}}$ .....		1
3.3 Characteristic value of friction, $f^*$ , as a function of the relative bearing width, $B/L$ , and the relative minimum lubricant film thickness, $h_{\min}/C_{\text{wed}}$ .....		4
3.4 Relative lubricant flow rates $Q_1^*$ and $Q_3^*$ as a function of the relative bearing width, $B/L$ , and the relative minimum lubricant film thickness, $h_{\min}/C_{\text{wed}}$ .....		5
3.5 Relative pressure centre coordinate or tilting pad supporting point $a_F^*$ as a function of the relative bearing width, $B/L$ , and the relative minimum lubricant film thickness, $h_{\min}/C_{\text{wed}}$ .....		8
<b>4 Effective dynamic viscosity of the lubricant, <math>\eta_{\text{eff}}</math>, as a function of the effective lubricant film temperature, <math>T_{\text{eff}}</math></b> .....		<b>10</b>
<b>Bibliography</b> .....		<b>12</b>