

# ISO 6526:2017-10 (E)

## Plain bearings - Pressed bimetallic half thrust washers - Features and tolerances

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>1</b>
<b>5</b>	<b>General tolerances .....</b>	<b>4</b>
<b>6</b>	<b>Tolerances for diameters and for heights .....</b>	<b>4</b>
<b>7</b>	<b>Total thickness .....</b>	<b>5</b>
<b>8</b>	<b>Locating lug .....</b>	<b>5</b>
<b>8.1</b>	<b>Lug width .....</b>	<b>5</b>
<b>8.2</b>	<b>Notch recess .....</b>	<b>6</b>
<b>8.3</b>	<b>Lug length .....</b>	<b>6</b>
<b>9</b>	<b>Grooves .....</b>	<b>6</b>
<b>9.1</b>	<b>Groove width .....</b>	<b>6</b>
<b>9.2</b>	<b>Wall thickness at the back of the groove .....</b>	<b>6</b>
<b>9.3</b>	<b>Groove position (with respect to the axis) .....</b>	<b>6</b>
<b>10</b>	<b>Joint faces .....</b>	<b>6</b>
<b>11</b>	<b>Fillet radii and chamfers .....</b>	<b>7</b>
<b>11.1</b>	<b>Radius on lug and joint faces and lug fillet radius .....</b>	<b>7</b>
<b>11.2</b>	<b>Joint face relief .....</b>	<b>7</b>
<b>11.3</b>	<b>Chamfer or radius between the sliding surface and side faces .....</b>	<b>7</b>
<b>11.4</b>	<b>Chamfer or radius between back and external side face .....</b>	<b>7</b>
<b>12</b>	<b>Flatness .....</b>	<b>7</b>
<b>13</b>	<b>Surface roughness .....</b>	<b>8</b>