

DIN ISO 20056-2:2019-07 (E)

Rolling bearings - Load ratings for hybrid bearings with rolling elements made of ceramic - Part 2: Static load ratings (ISO 20056-2:2017)

| Contents | | Page |
|--|--|-------------|
| National foreword | | 3 |
| National Annex NA (informative) Bibliography | | 4 |
| Foreword | | 5 |
| Introduction | | 6 |
| 1 Scope | | 7 |
| 2 Normative references | | 7 |
| 3 Terms and definitions | | 7 |
| 4 Symbols | | 8 |
| 5 Static load rating | | 9 |
| 5.1 General | | 9 |
| 5.2 Basic static radial load rating of radial ball bearings | | 9 |
| 5.3 Basic static axial load rating of thrust ball bearings | | 10 |
| 5.4 Basic static radial load rating of radial roller bearings | | 11 |
| 5.5 Basic static axial load rating of thrust roller bearings | | 11 |
| 5.6 Discontinuities in load ratings | | 11 |
| 5.7 Consideration of special material properties | | 11 |
| 6 Static equivalent load | | 11 |
| 6.1 General | | 11 |
| 6.2 Radial ball bearings | | 11 |
| 6.3 Thrust ball bearings | | 11 |
| 6.4 Radial roller bearings | | 11 |
| 6.5 Thrust roller bearings | | 11 |
| 7 Static safety factor | | 12 |
| Annex A (informative) Calculation of the Hertzian parameters for point contact | | 13 |
| Annex B (informative) Guide values of the factor f_0 for ball bearings | | 14 |
| Annex C (informative) Discontinuities in the calculation of basic static load ratings | | 16 |
| Annex D (informative) Material properties and material classification | | 17 |
| Bibliography | | 19 |
| Figures Figure D.1 -- Examples of typical current application areas for the different material classes and ball grades (arrows indicate potential overlap) | | 18 |
| Tables Table 1 -- Guideline values of static safety factor S_0 for hybrid ball bearings | | 12 |
| Table 2 -- Guideline values of static safety factor S_0 for hybrid roller bearings | | 12 |

| | |
|---|-----------|
| Table B.1 -- Guide values of factor f_0 for ball bearings | 14 |
| Table D.1 -- Correction factor for rolling elements made of ceramic with different elastic | 18 |