

ISO 7902-1:2020 (E)

Hydrodynamic plain journal bearings under steady-state conditions — Circular cylindrical bearings — Part 1: Calculation procedure

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and units
5	Basis of calculation, assumptions, and preconditions
5.1	Reynolds equation
5.2	Assumptions and preconditions
5.3	Boundary conditions
5.4	Basis of calculation
5.5	Permissible operational parameters
6	Calculation procedure
6.1	General
6.2	Freedom from wear
6.3	The limits of mechanical loading
6.4	The limits of thermal loading
6.5	Influencing factors
6.6	Reynolds number
6.7	Calculation factors
7	Definition of symbols
7.1	Load-carrying capacity
7.2	Frictional power loss
7.3	Lubricant flow rate
7.3.1	General
7.3.2	Lubricant feed elements
7.3.3	Lubrication grooves
7.3.4	Lubrication pockets
7.3.5	Lubricant flow rate
7.4	Heat balance
7.4.1	General
7.4.2	Heat dissipation by convection
7.4.3	Heat dissipation via the lubricant
7.5	Minimum lubricant film thickness and specific bearing load
7.6	Operational conditions
7.7	Further influencing factors
Annex A	(informative) Calculation examples
A.1	Example 1
A.2	Example 2
A.3	Example 3