ISO 12130-1:2021 (E)

Plain bearings — Hydrodynamic plain tilting pad thrust bearings under steady-state conditions — Part 1: Calculation of tilting pad thrust bearings

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols, terms and units

5 Fundamentals, assumptions and premises

6 Calculation procedure

- 6.1 Loading operations
- 6.1.1 General
- 6.1.2 Wear
- 6.1.3 Mechanical loading
- 6.1.4 Thermal loading
- 6.1.5 Outside influences
- 6.2 Coordinate of centre of pressure
- 6.3 Load-carrying capacity
- 6.4 Frictional power
- 6.5 Lubricant flow rate
- 6.6 Heat balance
- 6.6.1 General
- 6.6.2 Heat dissipation by convection
- 6.6.3 Heat dissipation by recirculating lubrication
- 6.6.4 Mixing processes in the lubrication recess
- 6.7 Minimum lubricant film thickness and specific bearing load
- 6.8 Operating conditions
- 6.9 Further influence factors

Annex A (informative) Examples of calculation

- A.1 Example: Tilting pad thrust bearing for constant load
- A.1.1 General
- A.1.2 Preliminary assumptions
- A.1.3 Calculation by means of the flow chart according to Figure 2
- A.1.4 Heat dissipation by convection
- A.1.4.1 First step
- A.1.4.2 Second step
- A.2 Example: Tilting-pad thrust bearing for speed-dependent load
- A.2.1 General
- A.2.2 Preliminary assumptions
- A.2.3 Calculation by means of the flow chart according to Figure 2
- A.2.4 Heat dissipation by convection
- A.2.4.1 First step
- A.2.4.2 Second step
- A.2.5 Heat dissipation by recirculating lubrication

Page count: 24