

DIN ISO 6526:2023-10 (E)

Plain bearings - Pressed bimetallic half thrust washers - Features and tolerances (ISO 6526:2017)

| Contents | | Page |
|---|---|-------------|
| National foreword | | 3 |
| National Annex NA (informative) Bibliography | | 4 |
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols | 6 |
| 5 | General tolerances | 9 |
| 6 | Tolerances for diameters and for heights | 9 |
| 7 | Total thickness | 10 |
| 8 | Locating lug | 10 |
| | 8.1 Lug width | 10 |
| | 8.2 Notch recess | 11 |
| | 8.3 Lug length | 11 |
| 9 | Grooves | 11 |
| | 9.1 Groove width | 11 |
| | 9.2 Wall thickness at the back of the groove | 11 |
| | 9.3 Groove position (with respect to the axis) | 11 |
| 10 | Joint faces | 11 |
| 11 | Fillet radii and chamfers | 12 |
| | 11.1 Radius on lug and joint faces and lug fillet radius | 12 |
| | 11.2 Joint face relief | 12 |
| | 11.3 Chamfer or radius between the sliding surface and side faces | 12 |
| | 11.4 Chamfer or radius between back and external side face | 12 |
| 12 | Flatness | 12 |
| 13 | Surface roughness | 13 |