

# ISO 21013-4:2012-06 (E)

## Cryogenic vessels - Pilot operated pressure relief devices - Part 4: Pressure-relief accessories for cryogenic service

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Requirements .....</b>	<b>3</b>
4.1	General .....	3
4.2	Design .....	3
4.3	Materials .....	4
<b>5</b>	<b>Qualification and testing .....</b>	<b>5</b>
5.1	Type approval .....	5
5.2	Type approval tests .....	6
5.3	Production testing .....	8
<b>6</b>	<b>Determination of the certified coefficient of discharge (K<sub>dr</sub>) .....</b>	<b>8</b>
<b>7</b>	<b>Set pressure tolerances .....</b>	<b>8</b>
<b>8</b>	<b>Re-seating pressure .....</b>	<b>8</b>
<b>9</b>	<b>Cleanliness .....</b>	<b>8</b>
<b>10</b>	<b>Marking .....</b>	<b>8</b>
10.1	Marking on the shell body of the main valve .....	8
10.2	Marking on the body of the pilot valve .....	8
10.3	Marking on an identification plate .....	9
10.4	Additional marking .....	9
<b>11</b>	<b>Sealing .....</b>	<b>9</b>
<b>Bibliography .....</b>		<b>10</b>